Kubescape

Kubernetes security scanner

CONCEPTS

Scan manifests before deploy and the live cluster afterwards: the same controls run on both.

Target cluster, files, Helm, image
↓ load
Framework NSA, MITRE, CIS: sets of controls
↓ evaluate
Controls C-xxxx checks, exceptions applied
↓ score
Report table, JSON, SARIF, HTML

Exceptions show up as exclude, not fail, so accepted risk stays visible in the report.

SCAN TARGETS

kubescape scan
Scan the cluster in your kubeconfig

kubescape scan *<path>*
Scan local YAML files or a directory

kubescape scan *<git-url>*
Scan a Git repository

kubescape scan *<chart-dir>*
Scan a Helm chart directory

--values *<file>*
Use a Helm values file when rendering

--set *<key=value>*
Override a Helm value

kubescape scan *<kustomize-dir>*
Scan a Kustomize directory

kubescape scan image *<image>*
Scan an image for vulnerabilities

kubescape scan image --username *<u>* **--password** *<p>* *<image>*
Scan from a private registry

--kubeconfig *<file>*
Use another kubeconfig

--include-namespaces *<list>*
Scan only these namespaces

--exclude-namespaces *<list>*
Skip these namespaces

FRAMEWORKS AND CONTROLS

kubescape scan framework *<name>*
Run all controls of a framework

kubescape scan framework nsa
NSA-CISA hardening guide

kubescape scan framework mitre
MITRE ATT&CK for Kubernetes

kubescape scan framework nsa,mitre
Run several frameworks at once

kubescape scan control *<id>*
Run a single control, e.g. C-0017

kubescape list controls
List available controls

kubescape list frameworks
List available frameworks

kubescape download controls-inputs
Fetch the tunable control parameters

--controls-config *<file>*
Scan with edited control parameters

VIEWS AND THRESHOLDS

--verbose
Show each failing resource and the fix

--view security
Default view when scanning files

--view resource
Group results by resource

--view control
Group results by control

--compliance-threshold *<pct>*
Exit 1 if compliance is below pct

--severity-threshold *<level>*
Fail on controls at this severity or above

Gate CI on --compliance-threshold: it is the documented, non-deprecated pass/fail switch.

OUTPUT

--format json --output *<file>*
Machine-readable report

--format sarif --output *<file>*
SARIF for code scanning

--format junit --output *<file>*
JUnit XML for CI test views

--format html --output *<file>*
Shareable HTML report

EXCEPTIONS

--exceptions *<file>*
Apply accepted-risk exceptions

posturePolicies
Controls or frameworks to exclude

resources
Match by kind, name, namespace or labels

Exception fields name, kind, namespace and controlID accept regex; resource labels do not.

Exclude a control in one namespace

```
[{"name": "allow-hostpath",
  "policyType":
"postureExceptionPolicy",
  "actions": ["alertOnly"],
  "resources": [{"designatorType":
"Attributes",
    "attributes": {"namespace":
"monitoring"}}],
  "posturePolicies":
[{"controlID": "C-0060"}]}]
```

FIX, PATCH AND POLICY

kubescape fix *<report.json>*
Auto-fix manifests from a JSON report

kubescape fix *<report.json>* **--dry-run**
Preview fixes without writing

CONFIG AND OFFLINE

kubescape config view
Show stored configuration

kubescape version
Print version