Kustomize Template-free manifests

CONCEPTS

Kustomize never edits your YAML: it reads a base, applies declared transformations and prints the result.

Base plain manifests
↓ resources
Overlay patches, images
↓ build
Rendered YAML stdout
↓ apply -k
Cluster

Layout convention: base/ holds shared manifests, overlays/<env>/ each hold a kustomization.yaml that lists ../../base under resources.

BUILD AND APPLY

kustomize build *<dir>*
Render a kustomization to stdout

kustomize build *<dir>* **-o** *<path>*
Write output to a file or directory

kubectl apply -k *<dir>*
Build and apply to the cluster

kubectl kustomize *<dir>*
Build using kubectl's bundled kustomize

kubectl diff -k *<dir>*
Show what apply would change

kubectl delete -k *<dir>*
Delete everything the build produces

kustomize build --enable-helm *<dir>*
Inflate helmCharts entries

CREATE AND EDIT

kustomize create
Write an empty kustomization.yaml

kustomize create --autodetect
Create it listing YAML files found

kustomize edit add resource *<path>*
Add a file or directory to resources

CREATE AND EDIT (cont.)

kustomize edit add patch --path *<file>* **--kind** *<kind>*
Add a patch entry

kustomize edit add configmap *<name>* **--from-literal=***<k>***=***<v>*
Add a generated ConfigMap

kustomize edit set image *<name>*=*<newname>*:*<tag>*
Change an image name and tag

kustomize edit set namespace *<ns>*
Set the namespace

kustomize edit set replicas *<name>*=*<n>*
Set a replica count

KUSTOMIZATION.YAML

Skeleton

```
apiVersion:
kustomize.config.k8s.io/v1beta1
kind: Kustomization
resources:
- ../../base
- extra.yaml
```

resources:
Files, directories or URLs to include

namespace: *<ns>*
Set namespace on every resource

labels:
Add labels, optionally to selectors

PATCHES

Strategic merge from a file

```
patches:
- path: patch.yaml
  target:
    kind: Deployment
    name: web
```

Inline JSON6902

```
patches:
- target: {kind: Deployment, name:
web}
  patch: |-
    - op: replace
      path: /spec/replicas
      value: 3
```

target: {kind, name, labelSelector}
Select what a patch applies to

op: add / replace / remove
JSON6902 operations

PATCHES (cont.)

path: /metadata/labels/a~1b
Escape / as ~1 in JSON paths

Without a target, a strategic merge patch matches by the apiVersion, kind and name written in the patch itself. JSON6902 always needs a target.

IMAGES AND GENERATORS

Images

```
images:
- name: nginx
  newName: registry.example/nginx
  newTag: "1.27"
```

ConfigMap from literals and files

```
configMapGenerator:
- name: app-config
  literals:
  - LOG_LEVEL=debug
  files:
  - app.properties
```

envs: [*<file>***.env]**
Load KEY=value lines as entries

secretGenerator:
Same fields as configMapGenerator, makes Secrets

behavior: create / replace / merge
How an overlay treats a base's generator

options: {disableNameSuffixHash: true}
Keep the plain name without a hash

REPLACEMENTS AND COMPONENTS

Copy a value into other fields

```
replacements:
- source:
    kind: ConfigMap
    name: app-config
    fieldPath: data.HOST
  targets:
  - select:
      kind: Deployment
    fieldPaths:
    - spec.template.spec.
containers.[name=web].env.[name=
HOST].value
```