lazydocker Terminal UI for Docker

START HERE

- `1-6` Jump to a panel
- `Up` / `Down` Move selection
- `[` / `]` Previous / next tab
- `m` View logs
- `E` Exec shell
- `r` Restart
- `x` Keybinding menu
- `q` Quit

CONCEPTS

Keys depend on the focused panel: d removes a container, an image or a volume depending on where you are. Press x for the live menu.

Project Services Containers Images Volumes Networks	Logs / Stats / Env / Config / Top of the selection

Left: side panels, right: main view with tabs

Services is only filled when lazydocker runs in a directory with a docker-compose file; otherwise use Containers.

Needs access to the Docker daemon (docker group or root).

NAVIGATE

`Up` / `Down` Move selection (also k / j)

`Left` / `Right` Previous / next panel (also h / l)

`1-6` Focus panel by number (1 projects … 6 networks)

`[` / `]` Previous / next tab of the main view

`Enter` Focus the main panel

`Esc` Return from the main panel

`/` Filter the current list

NAVIGATE (cont.)

`PgUp` / `PgDn` Scroll the main view

`Plus` / `_` Next / previous screen mode (normal, half, full)

`x` Open the keybinding menu

`q` Quit

CONTAINERS

`m` View logs (also in Project panel)

`E` Exec shell in the container

Needs a shell inside the image; distroless images have none.

`r` Restart

`s` Stop

`p` Pause

`a` Attach to the container

`e` Hide / show stopped containers

`w` Open in browser (first port, assumed http)

SERVICES

`u` Up the selected service

`S` Start the service

`U` Up the whole project

`D` Down the whole project

`R` Restart options menu

SERVICES (cont.)

Services also take d, s, p, r, a, m, E and w, like containers (d removes containers, not the service).

IMAGES, VOLUMES, NETWORKS

`d` Remove the selected item (container, image, …)

`b` Bulk commands (prune unused ones)

`c` Run a predefined custom command (any panel)

The Images panel tabs show config and layers; Volumes and Networks show their config. Use [/] to switch.

CONFIG

`o` Open the lazydocker config (Project panel)

Config lives in config.yml under the lazydocker config dir (~/.config/lazydocker on Linux). lazydocker --config prints the directory.

config.yml: custom command for containers

```
customCommands:
  containers:
    - name: bash
      attach: true
      command: 'docker exec -it
{{ .Container.ID }} bash'
      serviceNames: []
```

CONFIG (cont.)

config.yml: tweak UI and logs

```
gui:
  scrollHeight: 2
  sidePanelWidth: 0.333
logs:
  tail: '200'
  since: '60m'
```

Custom commands show up with c on the matching panel; templates can use {{ .Container.ID }} and similar fields.

RECIPES

Tail logs of a crashing container

```
# 3 to focus Containers, pick
it
m         # logs tab
/         # filter if needed
r         # restart and watch
```

Shell into a service

```
# in a compose project dir
lazydocker
2         # Services panel
E         # exec shell
```

Free disk space

```
4         # Images panel
b         # bulk commands: prune
images
5         # Volumes
b         # prune unused volumes
```

Bounce a stack

```
lazydocker
D         # down project
U         # up project
```