OpenLDAP client tools Query LDAP directories

START HERE

`ldapsearch -x -H ldap://<host> -b <base>`
Anonymous search

`ldapsearch -LLL -x -b <base>`
Clean LDIF output

`ldapsearch -x -H <uri> -D <binddn> -W -b <base>`
Authenticated search

`ldapsearch -x -s base -b "" -H <uri> +`
Probe the server (rootDSE)

`ldapsearch -x -b <base> "(uid=<name>)"`
Filter entries

`ldapwhoami -x -H <uri> -D <binddn> -W`
Who am I bound as?

`ldapsearch -x -b <base> "(cn=*)" cn mail`
Pick attributes

`ldapmodify -x -H <uri> -D <binddn> -W -f <file>`
Apply an LDIF change

Connect -H uri, -Z StartTLS → *bind* → **Bind** -x -D -W or SASL → *search* → **Search** -b base -s scope filter → *return* → **Entries** attrs, LDIF output

One ldapsearch run

CONCEPTS

Always add -x unless you want SASL: without it the tools try SASL and often fail with confusing errors.

Directory data is a tree: a DN names an entry, the base picks the subtree, the scope picks how deep.

Put the filter in quotes; shell characters like ( ) and * would otherwise be eaten.

CONNECT AND BIND

`-H ldap://<host>[:<port>]`
Server URI (plain or StartTLS)

`-H ldaps://<host>`
TLS from the first byte

`-H ldapi:///`
Local socket (as root, with -Y EXTERNAL)

`-x`
Simple bind instead of SASL

`-D <binddn>`
Bind as this DN

`-W`
Prompt for the password

`-y <file>`
Read password from a file

`-w <password>`
Password on command line
Visible in the process list and shell history; prefer -W or -y.

`-ZZ`
StartTLS, fail if it cannot be used
-Z alone continues in cleartext if StartTLS fails.

`-Y EXTERNAL -H ldapi:///`
SASL EXTERNAL over the local socket

`-Y GSSAPI`
Kerberos login

`-P 3`
Pin LDAP protocol version

`-o nettimeout=<s>`
Network timeout in seconds

SEARCHING

`-b <base>`
Search base DN

`-b ""`
Empty base: rootDSE with -s base

`-s base / one / sub / children`
Search scope (default sub)

`"(<attr>=<value>)"`
Equality filter

`"(<attr>=<pre>*)"`
Substring/wildcard match

`"(<attr>=*)"`
Attribute is present

`"(&(<f1>)(<f2>))"`
AND of filters

`"(|(<f1>)(<f2>))"`
OR of filters

`"(!(<f>))"`
Negate a filter

`"(<attr>≥<n>)"`
Greater or equal (<= for less)

`"(<attr>~=<value>)"`
Approximate match

`-z <n>`
Max entries returned

`-l <seconds>`
Time limit for the search

`-a always`
Dereference aliases

`\28 \29 \2a \5c`
Escape ( ) * \ in values

`-f <file> "(uid=%s)"`
One search per input line

ATTRIBUTES AND OUTPUT

`... <filter> cn mail`
Return only listed attributes

`"*" "+"`
User plus operational attributes

`1.1`
Return DNs only

`-LLL`
Plain LDIF, no comments or version

`-L`
LDIF v1 with comments

`-A`
Attribute names only, no values

ATTRIBUTES AND OUTPUT (cont.)

`-S <attr>`
Sort entries client-side

`-o ldif_wrap=no`
Don't wrap long LDIF lines

`-t`
Write binary values to temp files

`-u`
Show user-friendly DNs

`-E pr=<n>/noprompt`
Paged results
Needed for directories that cap result size; combine with -z 0 or leave unset.

`-E sss=<attr>`
Server-side sort

`-E vlv=<b>/<a>/<off>/<cnt>`
Virtual list view

`-v`
Verbose diagnostics

`-d 1`
Debug (needs a debug build)

`-n`
Dry run, no search

CHANGE ENTRIES

`ldapadd -x -D <binddn> -W -f <file>`
Add entries from LDIF

`ldapmodify -x -D <binddn> -W -f <file>`
Apply LDIF changes

`ldapdelete -x -D <binddn> -W "<dn>"`
Delete an entry

`ldapdelete -r "<dn>"`
Delete a subtree

`ldapmodrdn -x -D <binddn> -W "<dn>" "<newrdn>"`
Rename an entry

`ldappasswd -x -D <binddn> -W -S "<dn>"`
Set a password (prompts)

`ldappasswd -A -S`
Also prompt for the old password

`ldapwhoami -x -D <binddn> -W`
Show the identity after bind

`ldapmodify -c -S <skipfile>`
Keep going, save failed records

CHANGE ENTRIES (cont.)

`ldapmodify -a`
Treat input as adds

`ldapmodify -n -v`
Dry run with verbose output

`ldapcompare -x "<dn>" <attr>:<value>`
Test an attribute value

LDIF change record

Line	Meaning
`dn: <dn>`	Entry to change
`changetype: modify`	Modify (also add, delete, modrdn)
`add: / replace: / delete: <attr>`	Operation on an attribute
`-`	Ends one operation block

Separate records in an LDIF file with a blank line; the lone - line closes each modify block.

RECIPES

Export a subtree

```
# dump a whole subtree to a file
ldapsearch -x -LLL -H ldaps://
<host> -D <binddn> -W \
  -b "<base>" "(objectClass=*)"
> backup.ldif
```

Discover the base DN

```
# find the naming contexts the
server offers
ldapsearch -x -LLL -H ldap://
<host> -s base -b "" \
  namingContexts
supportedSASLMechanisms
```

Query over StartTLS

```
# members of a group, only mail
addresses
ldapsearch -x -LLL -ZZ -H
ldap://<host> -D <binddn> -W -b
<base> \
  "(&(objectClass=person)(
memberOf=<groupdn>))" mail
```

Edit one attribute

```
# change a mail address
cat > fix.ldif <<'EOF'
dn: <dn>
changetype: modify
replace: mail
mail: <new>
EOF
ldapmodify -x -D <binddn> -W -f
fix.ldif
```