OpenLDAP client tools Query LDAP directories

CONCEPTS

Connect -H uri, -Z StartTLS
↓ bind
Bind -x -D -W or SASL
↓ search
Search -b base -s scope filter
↓ return
Entries attrs, LDIF output

One ldapsearch run

> Always add -x unless you want SASL: without it the tools try SASL and often fail with confusing errors.

CONNECT AND BIND

-H ldap://<*host*>**[:**<*port*>**]**
Server URI (plain or StartTLS)

-H ldaps://<*host*>
TLS from the first byte

-x
Simple bind instead of SASL

-D <*binddn*>
Bind as this DN

-W
Prompt for the password

-ZZ
StartTLS, fail if it cannot be used

SEARCHING

-b <*base*>
Search base DN

-s base / one / sub / children
Search scope (default sub)

"(<*attr*>**=**<*value*>**)"**
Equality filter

"(<*attr*>**=**<*pre*>***)"**
Substring/wildcard match

"(&(<*f1*>**)(**<*f2*>**))"**
AND of filters

"(|(<*f1*>**)(**<*f2*>**))"**
OR of filters

ATTRIBUTES AND OUTPUT

... <*filter*> **cn mail**
Return only listed attributes

"*" "+"
User plus operational attributes

1.1
Return DNs only

-LLL
Plain LDIF, no comments or version

-S <*attr*>
Sort entries client-side

-E pr=<*n*>**/noprompt**
Paged results

CHANGE ENTRIES

ldapadd -x -D <*binddn*> **-W -f** <*file*>
Add entries from LDIF

ldapmodify -x -D <*binddn*> **-W -f** <*file*>
Apply LDIF changes

ldapdelete -x -D <*binddn*> **-W "**<*dn*>**"**
Delete an entry

ldappasswd -x -D <*binddn*> **-W -S "**<*dn*>**"**
Set a password (prompts)

ldapwhoami -x -D <*binddn*> **-W**
Show the identity after bind

LDIF change record

Line	Meaning
`dn: <dn>`	Entry to change
`changetype: modify`	Modify (also add, delete, modrdn)
`add: / replace: / delete: <attr>`	Operation on an attribute
`-`	Ends one operation block