OpenLDAP client tools

Query LDAP directories

CONCEPTS

Connect -H uri, -Z StartTLS
↓ bind
Bind -x -D -W or SASL
↓ search
Search -b base -s scope filter
↓ return
Entries attrs, LDIF output

One ldapsearch run

> Always add -x unless you want SASL: without it the tools try SASL and often fail with confusing errors.

> Directory data is a tree: a DN names an entry, the base picks the subtree, the scope picks how deep.

> Put the filter in quotes; shell characters like ( ) and * would otherwise be eaten.

CONNECT AND BIND

-H ldap://*<host>***[:***<port>***]**
Server URI (plain or StartTLS)

-H ldaps://*<host>*
TLS from the first byte

-H ldapi:///
Local socket (as root, with -Y EXTERNAL)

-x
Simple bind instead of SASL

-D *<binddn>*
Bind as this DN

-W
Prompt for the password

-y *<file>*
Read password from a file

-w *<password>*
Password on command line

-ZZ
StartTLS, fail if it cannot be used

SEARCHING

-b *<base>*
Search base DN

-b ""
Empty base: rootDSE with -s base

SEARCHING (cont.)

-s base / one / sub / children
Search scope (default sub)

"(*<attr>***=***<value>***)"**
Equality filter

"(*<attr>***=***<pre>****)"**
Substring/wildcard match

"(*<attr>***=*)"**
Attribute is present

"(&(*<f1>***)(***<f2>***))"**
AND of filters

"(|(*<f1>***)(***<f2>***))"**
OR of filters

"(!(*<f>***))"**
Negate a filter

"(*<attr>* **≥** *<n>***)"**
Greater or equal (<= for less)

-z *<n>*
Max entries returned

-l *<seconds>*
Time limit for the search

\28 \29 \2a \5c
Escape ( ) * \ in values

ATTRIBUTES AND OUTPUT

... *<filter>* **cn mail**
Return only listed attributes

"*" "+"
User plus operational attributes

1.1
Return DNs only

-LLL
Plain LDIF, no comments or version

-L
LDIF v1 with comments

-S *<attr>*
Sort entries client-side

-o ldif_wrap=no
Don't wrap long LDIF lines

-E pr=*<n>***/noprompt**
Paged results

-v
Verbose diagnostics

CHANGE ENTRIES

ldapadd -x -D *<binddn>* **-W -f** *<file>*
Add entries from LDIF

ldapmodify -x -D *<binddn>* **-W -f** *<file>*
Apply LDIF changes

ldapdelete -x -D *<binddn>* **-W "***<dn>***"**
Delete an entry

ldappasswd -x -D *<binddn>* **-W -S "***<dn>***"**
Set a password (prompts)

ldapwhoami -x -D *<binddn>* **-W**
Show the identity after bind

ldapmodify -a
Treat input as adds

ldapmodify -n -v
Dry run with verbose output

LDIF change record

Line	Meaning
`dn: <dn>`	Entry to change
`changetype: modify`	Modify (also add, delete, modrdn)
`add: / replace: / delete: <attr>`	Operation on an attribute
`-`	Ends one operation block

> Separate records in an LDIF file with a blank line; the lone - line closes each modify block.

RECIPES

Export a subtree

```
# dump a whole subtree to a file
ldapsearch -x -LLL -H ldaps://
<host> -D <binddn> -W \
  -b "<base>" "(objectClass=*)" >
backup.ldif
```

Discover the base DN

```
# find the naming contexts the
server offers
ldapsearch -x -LLL -H ldap://
<host> -s base -b "" \
  namingContexts
supportedSASLMechanisms
```