LLDB LLVM debugger

CONCEPTS

Compile with -g (and -O0 for sane stepping), otherwise LLDB has no source lines or local variables.

Commands are noun verb (breakpoint set, frame select); most have short aliases such as b, n, s, c, bt, p, f.

START AND ATTACH

`lldb` *`<prog>`*
Load a program

`lldb --` *`<prog> <args>`*
Load a program with arguments

`lldb -p` *`<pid>`*
Attach to a running process

`run [args]`
Start the program

`quit`
Leave LLDB

BREAKPOINTS

`b` *`<func>`*
Break at a function

`b` *`<file>`*`:`*`<line>`*
Break at a line of a file

`breakpoint set --name` *`<func>`* **`--condition '`***`<cond>`***`'`**
Break only when the condition holds

`breakpoint list`
List breakpoints and hit counts

`breakpoint delete` *`<n>`*
Delete a breakpoint

WATCHPOINTS

`watchpoint set variable` *`<var>`*
Stop when a variable changes

RUN CONTROL

`c`
Continue until the next stop

RUN CONTROL (cont.)

`n`
Step over the next line

`s`
Step into the next line

`finish`
Run until the current function returns

STACK AND THREADS

`bt`
Backtrace of the current thread

`bt all`
Backtrace of every thread

`frame select` *`<n>`*
Switch to frame n

`up`
Go to the caller frame

`down`
Go back toward the callee frame

`thread list`
List threads

INSPECT DATA

`frame variable`
Show arguments and locals

`frame variable` *`<var>`*
Show one variable

`p` *`<expr>`*
Evaluate a C/C++ expression

FROM GDB

GDB to LLDB

GDB	LLDB
`break foo`	b foo
`rbreak <re>`	breakpoint set -r <re>
`info locals`	frame variable
`info break`	breakpoint list
`watch <var>`	watchpoint set variable <var>
`info threads`	thread list
`disassemble`	disassemble --frame
`info registers`	register read