mdadm Linux software RAID

Disks / partitions components → `--create` → **/dev/md0** md array → `mkfs` → **Filesystem** ext4, xfs, LVM… → `mount` → **In use** watch /proc/mdstat

CONCEPTS

RAID is not a backup: it survives a disk failure, not deletion, corruption or a dead controller.

Create, grow and add start a background resync; the array is usable meanwhile but slower and not yet redundant.

Most commands need root and many write superblocks: double-check device names with lsblk first.

INSPECT

`cat /proc/mdstat`
Show arrays, members and sync progress

`mdadm --detail <md>`
Array state, level, members, UUID

`mdadm --examine <dev>`
Read the RAID superblock of a member

`mdadm --query <dev>`
Is this device an array or a member?

`mdadm --detail --scan`
One-line summary per active array

INSPECT (cont.)

`mdadm --examine --scan`
Find arrays on member superblocks

`watch cat /proc/mdstat`
Follow sync progress live

CREATE

`mdadm --create <md> --level=1 --raid-devices=2 <dev1> <dev2>`
Mirror (RAID1) of two devices

`mdadm --create <md> --level=5 --raid-devices=3 <dev1> <dev2> <dev3>`
RAID5: striping with parity

`mdadm --create <md> --level=6 --raid-devices=4 <devs>`
RAID6: survives two failures

`mdadm --create <md> --level=0 --raid-devices=2 <dev1> <dev2>`
RAID0: striping, no redundancy

`mdadm --create <md> --level=10 --raid-devices=4 <devs>`
RAID10: mirrored stripes

`mdadm --create ... --spare-devices=1 <devs>`
Include a hot spare

CREATE (cont.)

`mdadm --create ... --bitmap=internal`
Write-intent bitmap, faster resync

Prefer partitions of type Linux RAID, or whole disks, of equal size; the smallest member sets the size.

FAIL, REPLACE, REPAIR

`mdadm <md> --fail <dev>`
Mark a member as faulty

`mdadm <md> --remove <dev>`
Remove a failed member

`mdadm <md> --add <dev>`
Add a disk; rebuild starts

`mdadm <md> --re-add <dev>`
Re-add a recently removed member

`mdadm <md> --replace <dev> --with <spare>`
Swap a disk while it is still healthy

`mdadm <md> --fail detached --remove detached`
Drop members whose device vanished

FAIL, REPLACE, REPAIR (cont.)

`mdadm --zero-superblock <dev>`
Erase RAID metadata from a disk

`echo check > /sys/block/<md>/md/sync_action`
Scrub the array for mismatches

After a disk swap, copy the partition layout first (sfdisk -d | sfdisk), then --add the partition.

ASSEMBLE AND STOP

`mdadm --assemble --scan`
Assemble arrays from config or superblocks

`mdadm --assemble <md> <dev1> <dev2>`
Assemble one array from given members

`mdadm --stop <md>`
Deactivate an array (unmount first)

`mdadm --stop --scan`
Stop every array not in use

`mdadm --assemble --run <md> <devs>`
Start even with missing members

GROW AND RESHAPE

`mdadm --grow <md> --raid-devices=<n>`
Change the number of active members

`mdadm --grow <md> --size=max`
Use all space after bigger members

`mdadm --grow <md> --bitmap=internal`
Add a write-intent bitmap

After growing, extend the filesystem (resize2fs, xfs_growfs) or the LVM layer on top.

CONFIG AND MONITORING

`mdadm --detail --scan >> /etc/mdadm/mdadm.conf`
Persist array definitions

`mdadm --monitor --scan --daemonise`
Run the monitor in the background

`systemctl status mdmonitor`
Check the monitor service

`update-initramfs -u`
Refresh initramfs (Debian/Ubuntu)