mise Tool versions, env and tasks

CONCEPTS

> mise manages tool versions, env variables and tasks from one mise.toml per project. Commit it so everyone gets the same setup.

mise.toml [tools] [env] [tasks]
↓ `mise install`
Installed tools in the mise data dir
↓ `activate or shims`
PATH + env per directory
↓ `mise run`
Tasks run with these tools

What mise does in a project

> Activation (mise activate in your shell rc) updates PATH on every prompt. Shims suit IDEs and scripts that skip rc files; mise exec and mise run need neither.

INSTALL AND ACTIVATE

`curl -fsSL https://mise.run | sh`
Install mise to ~/.local/bin

`eval "$(mise activate bash)"`
Activate in bash (put in ~/.bashrc)

`eval "$(mise activate zsh)"`
Activate in zsh (put in ~/.zshrc)

TOOLS

`mise use <tool>@<version>`
Install and add to mise.toml

`mise use -g <tool>@<version>`
Same, in the global config

`mise install`
Install every tool the config lists

`mise ls`
List installed and active tools

`mise ls-remote <tool>`
Versions available to install

`mise upgrade`
Upgrade within configured ranges

RUNNING WITH TOOLS

`mise exec <tool>@<version> -- <cmd>`
Run a command with that tool

`mise x -- <cmd>`
Run with the project's tools and env

`mise shell <tool>@<version>`
Use a version in this shell only

ENVIRONMENT

`mise set <KEY>=<value>`
Set a variable in mise.toml

`mise set`
List variables and their sources

TASKS

`mise run <task>`
Run a task and its dependencies

`mise <task>`
Shorthand for mise run <task>

`mise tasks`
List tasks

Task fields in [tasks.<name>]

Field	Effect
`run`	Command, or array run in order
`description`	Shown in mise tasks
`depends`	Tasks that must succeed first
`alias`	Short name for mise run
`dir`	Working directory
`env`	Variables for this task only
`sources / outputs`	Skip when outputs are current
`hide`	Hide from the list, still runnable
`confirm`	Ask before running

CONFIG AND TRUST

`mise trust`
Trust the nearest untrusted config

`mise doctor`
Check the setup for problems