mitmproxy Intercepting HTTP(S) proxy

START HERE

`mitmproxy`
Start proxy on :8080

r
Replay flow

i
Set intercept filter

?
Context help

f
Filter the flow list

Enter
Open flow

e
Edit a flow part

a
Resume intercepted flow

Front ends

Tool	Use
`mitmproxy`	Interactive terminal UI
`mitmweb`	Web UI on :8081
`mitmdump`	Headless, like tcpdump for HTTP

CONCEPTS

Only intercept traffic from devices and apps you own or are explicitly authorised to inspect.

Three front ends share one engine: mitmproxy (TUI), mitmweb (browser UI) and mitmdump (no UI, scripts and files).

Client proxy set to :8080
↓ HTTP(S)
mitmproxy decrypts with its CA
↓ re-encrypted
Server real destination
Where mitmproxy sits

HTTPS only works once the client trusts the mitmproxy CA; browse to mitm.it through the proxy to install it.

FLOW LIST

j / **k** Move down / up

g / **G** Go to first / last flow

Enter Open the focused flow

q Back / leave current view

Space Page down

f Set the view filter

m Mark / unmark flow

FLOW LIST (cont.)

M Show only marked flows

U Clear all marks

d Delete flow from view

D Duplicate flow

z Clear the whole flow list

F Toggle focus follow (tail)

n Create a new request flow

FLOW VIEW

Tab
Switch request / response / detail

e
Edit URL, header, body or method

m
Choose content view (JSON, hex...)

z
Toggle body encoding (gzip etc.)

v
Open body in external viewer

p / **Space**
Previous / next flow

V Revert edits to flow

INTERCEPT AND REPLAY

i
Set intercept filter, e.g. ~u api & ~q

I Toggle intercept on / off

a
Resume the intercepted flow

A
Resume all intercepted flows

r
Replay request to the server

x
Export flow (curl, httpie, raw...)

b Save response body to file

SAVE, LOAD, GLOBAL

w Save listed flows to file

L Load flows from file

W Stream flows to file live

E Open event log

O Open options

: Command prompt

B
Launch an attached browser

? Context-sensitive help

SAVE, LOAD, GLOBAL (cont.)

Q Quit immediately

FILTER EXPRESSIONS

`~u` *`<regex>`*
Match URL

`~d` *`<regex>`*
Match domain

`~m` *`<regex>`*
Match method

`~c` *`<code>`*
Match response status code

`~h` *`<regex>`*
Match any header

`~b` *`<regex>`*
Match any body

`~t` *`<regex>`*
Match Content-Type

`~q` / `~s`
Request without / with response

`~e`
Match flows with errors

`!` / `&` / `|` / `( )`
Not, and, or, grouping

Regexes are case-insensitive. A bare word with no ~ is matched against the URL.

COMMAND LINE

`mitmproxy -p` *`<port>`*
Listen on another port

`mitmweb`
Web interface

`mitmdump -w` *`<file>`*
Record flows to file

`mitmproxy -r` *`<file>`*
Open a saved flow file

`mitmdump -nr` *`<file>`*
Read file without proxying

`mitmdump "`*`<filter>`***`"`**
Show only matching flows

`--mode regular`
Explicit proxy (default)

`--mode local[:`*`<app>`***`]`**
Capture local apps by name or PID

`--mode reverse:`*`<url>`***
Front a single server

`--mode transparent`
Network-level capture (Linux, macOS)

`-s` *`<script.py>`*
Load an addon script

`--set` *`<option>`*`=`*`<value>`*
Set any option

`--ignore-hosts` *`<regex>`*
Do not decrypt matching hosts
Use for apps that pin certificates.

CERTIFICATES

`http://mitm.it`
Download CA via the proxy

`~/.mitmproxy/mitmproxy-ca-cert.pem`
CA certificate (non-Windows)

`curl --cacert` *`<ca.pem>`* **`-x`** *`<proxy> <url>`*
Trust CA for one curl call

The CA is generated per installation on first start. Remove it from devices when you finish testing.

RECIPES

Capture then inspect later

```
mitmdump -w session.flows
# use the app through the
proxy, Ctrl+C
mitmproxy -r session.flows
```

Watch one app's API calls

```
mitmproxy --mode local:curl
# in the TUI: f  ~d
api.example.com & ~m POST
curl https://api.example.com/x
```

Reverse proxy a local service

```
mitmweb --mode reverse:http://
localhost:3000 \
  --listen-port 8080
```

Modify with an addon

```
# addon.py
def response(flow):
    flow.response.headers["x-
seen"] = "1"
# mitmdump -s addon.py
```