mitmproxy Intercepting HTTP(S) proxy

START HERE

`mitmproxy`
Start proxy on :8080

e
Edit a flow part

i
Set intercept filter

a
Resume intercepted flow

f
Filter the flow list

r
Replay flow

Enter
Open flow

?
Context help

Front ends

Tool	Use
`mitmproxy`	Interactive terminal UI
`mitmweb`	Web UI on :8081
`mitmdump`	Headless, like tcpdump for HTTP

CONCEPTS

Only intercept traffic from devices and apps you own or are explicitly authorised to inspect.

Three front ends share one engine: mitmproxy (TUI), mitmweb (browser UI) and mitmdump (no UI, scripts and files).

Client proxy set to :8080
↓ HTTP(S)
mitmproxy decrypts with its CA
↓ re-encrypted
Server real destination
Where mitmproxy sits

HTTPS only works once the client trusts the mitmproxy CA; browse to mitm.it through the proxy to install it.

FLOW LIST

j / **k** Move down / up

g / **G** Go to first / last flow

Enter Open the focused flow

q Back / leave current view

Space Page down

f Set the view filter

m Mark / unmark flow

M Show only marked flows

U Clear all marks

o Choose flow list order

v Reverse list order

d Delete flow from view

D Duplicate flow

z Clear the whole flow list

Z
Purge flows hidden by filter

F Toggle focus follow (tail)

n Create a new request flow

X Kill a flow in progress

; Add a comment to flow

FLOW VIEW

Tab
Switch request / response / detail

e
Edit URL, header, body or method

FLOW VIEW (cont.)

m
Choose content view (JSON, hex...)

z
Toggle body encoding (gzip etc.)

v
Open body in external viewer

p / **Space**
Previous / next flow

V Revert edits to flow

Ctrl + **Right** / **Ctrl** + **Left**
Next / previous pane

- Cycle layout

INTERCEPT AND REPLAY

i
Set intercept filter, e.g. ~u api & ~q

I Toggle intercept on / off

a
Resume the intercepted flow

A
Resume all intercepted flows

r
Replay request to the server

S
Start server replay of a flow set
Serves saved responses instead of contacting servers.

| Run a script on this flow

x
Export flow (curl, httpie, raw...)

b Save response body to file

SAVE, LOAD, GLOBAL

w Save listed flows to file

L Load flows from file

W Stream flows to file live

E Open event log

O Open options

: Command prompt

B
Launch an attached browser

C List commands

K Show key bindings

? Context-sensitive help

Q Quit immediately

FILTER EXPRESSIONS

`~u <regex>`
Match URL

`~d <regex>`
Match domain

`~m <regex>`
Match method

`~c <code>`
Match response status code

`~h <regex>`
Match any header

`~b <regex>`
Match any body

`~bq / ~bs <regex>`
Match request / response body

`~hq / ~hs <regex>`
Match request / response header

`~t <regex>`
Match Content-Type

`~q / ~s`
Request without / with response

`~e`
Match flows with errors

`! / & / | / ( )`
Not, and, or, grouping

Regexes are case-insensitive. A bare word with no ~ is matched against the URL.

COMMAND LINE

`mitmproxy -p <port>`
Listen on another port

`mitmweb`
Web interface

`mitmdump -w <file>`
Record flows to file

`mitmproxy -r <file>`
Open a saved flow file

`mitmdump -nr <file>`
Read file without proxying

`mitmdump "<filter>"`
Show only matching flows

`--mode regular`
Explicit proxy (default)

`--mode local[:<app>]`
Capture local apps by name or PID

`--mode reverse:<url>`
Front a single server

`--mode transparent`
Network-level capture (Linux, macOS)

`--mode socks5`
Run as SOCKS5 proxy

COMMAND LINE (cont.)

`--mode wireguard`
WireGuard server for devices

`--mode upstream:<url>`
Chain to another proxy

`-s <script.py>`
Load an addon script

`--set <option>=<value>`
Set any option

`--ignore-hosts <regex>`
Do not decrypt matching hosts
Use for apps that pin certificates.

`--allow-hosts <regex>`
Only decrypt matching hosts

`--set block_global=false`
Accept non-local clients

`--set client_replay=<file>`
Replay flows at startup

`--set server_replay=<file>`
Serve responses from a flow file

CERTIFICATES

`http://mitm.it`
Download CA via the proxy

`~/.mitmproxy/mitmproxy-ca-cert.pem`
CA certificate (non-Windows)

`~/.mitmproxy/mitmproxy-ca.pem`
CA with private key: keep secret

`curl --cacert <ca.pem> -x <proxy> <url>`
Trust CA for one curl call

The CA is generated per installation on first start. Remove it from devices when you finish testing.

RECIPES

Capture then inspect later

```
mitmdump -w session.flows
# use the app through the
proxy, Ctrl+C
mitmproxy -r session.flows
```

Watch one app's API calls

```
mitmproxy --mode local:curl
# in the TUI: f  ~d
api.example.com & ~m POST
curl https://api.example.com/x
```

Reverse proxy a local service

```
mitmweb --mode reverse:http://
localhost:3000 \
  --listen-port 8080
```

Modify with an addon

```
# addon.py
def response(flow):
    flow.response.headers["x-
seen"] = "1"
# mitmdump -s addon.py
```