mongosh MongoDB shell

CONCEPTS

> mongosh is a JavaScript shell: db is the current database, db.<name> a collection, and any JS works.

Deployment server or cluster
- **Database** db / use <db>
  - **Collection** db.users
    - **Document** BSON object

CONNECT

mongosh
Connect to localhost:27017

mongosh "mongodb://*<host>***:27017/***<db>***"**
Connect with a URI

mongosh --host *<host>* **--port** *<port>* **-u** *<user>* **-p**
Connect with options, prompt for password

--eval "*<js>***"** *<uri>*
Run JavaScript and exit

mongosh *<uri>* *<file.js>*
Run a script file then exit

exit / quit()
Leave the shell

INSPECT

show dbs
List databases

use *<db>*
Switch database

db
Print the current database name

show collections
List collections

db.*<coll>***.countDocuments({})**
Count matching documents

db.*<coll>***.getIndexes()**
List indexes

READ

db.*<coll>***.find()**
All documents (first batch)

db.*<coll>***.find({** *<field>***:** *<value>* **})**
Match on equality

db.*<coll>***.findOne({** *<filter>* **})**
First match as one document

db.*<coll>***.find({}, { *<f>*: 1 })**
Projection: pick fields

db.*<coll>***.find().sort({** *<f>*: -1 **})**
Sort, 1 ascending, -1 descending

db.*<coll>***.find().limit(***<n>***)**
Cap results; chain .skip(<n>) to page

db.*<coll>***.find(***<filter>***).explain("executionStats")**
Show how the query ran

WRITE

db.*<coll>***.insertOne({** *<doc>* **})**
Insert one document

db.*<coll>***.insertMany([{ }, { }])**
Insert several documents

db.*<coll>***.updateOne(***<filter>***, { $set: { *<f>*: *<v>* } })**
Change first match

db.*<coll>***.deleteOne(***<filter>***)**
Delete first match

db.*<coll>***.deleteMany(***<filter>***)**
Delete all matches

AGGREGATION

db.*<coll>***.aggregate([***<stage>***])**
Run a pipeline of stages

{ $group: { _id: "$*<f>***", n: { $sum: 1 } } }**
Group and count

INDEXES

db.*<coll>***.createIndex({** *<f>*: 1 **})**
Create an ascending index