NATS CLI Messaging and JetStream

CONCEPTS

> Subjects are dot-separated tokens. * matches one token, > matches all remaining tokens.

Publisher nats pub
↓ subject
Server routes by subject
↓ captured by
Stream JetStream, stored
↓ consumer reads
Consumer cursor + acks

> Plain pub/sub is fire and forget: a subscriber that is offline misses the message. Streams (JetStream) keep it.

CONNECT AND CONTEXTS

`nats context add <name> --server <url> --select`
Save a server as a context

`nats context ls`
List saved contexts

`nats context select <name>`
Switch context

`nats --server <url> <command>`
Use a server without a context

PUBLISH AND SUBSCRIBE

`nats pub <subject> "<msg>"`
Publish a message

`nats sub <subject>`
Print messages as they arrive

`nats sub "<prefix>.>"`
Subscribe to a whole subject tree

REQUEST AND REPLY

`nats request <subject> "<msg>"`
Send a request, print the reply

`nats reply "<subject>" "<body>"`
Answer requests with a fixed body

SERVER AND ACCOUNT

`nats account info`
Show account limits and usage

`nats-server -js`
Start a local server with JetStream

STREAMS

`nats stream add <name> --subjects "<s>.>" --defaults`
Create a stream

`nats stream ls`
List streams

`nats stream info <name>`
Show config and state

`nats stream view <name>`
Browse stored messages

`nats stream rm <name>`
Delete a stream

CONSUMERS

`nats consumer add <stream> <consumer> --pull --defaults`
Create a durable pull consumer

`nats consumer next <stream> <consumer> --count <n>`
Fetch and ack n messages

`nats consumer ls <stream>`
List a stream's consumers

KEY-VALUE STORE

`nats kv add <bucket>`
Create a bucket

`nats kv put <bucket> <key> <value>`
Set a key

`nats kv get <bucket> <key>`
Read a key

`nats kv ls`
List buckets

`nats kv watch <bucket>`
Stream changes live