NeoMutt Terminal email client

Index message list → Enter → **Pager** read one mail → r / m → **Compose** headers, attach → y → **Sent** back to index

CONCEPTS

Keys depend on the screen: the index lists mail, the pager shows one message, compose edits one. Press ? on any screen for its live key list.

Deletes and flag changes are only marked until you sync with $ or leave the folder; u undeletes before that.

Esc in a key means Alt (or press Esc first). Defaults can differ: your config may rebind keys, so check ? first.

MOVING AROUND

j / **k**
Next / previous message

Enter Open the message

Space
Page down, then next message

- / **Backspace**
Page up / line up in the pager

q
Leave pager or folder, then quit

MOVING AROUND (cont.)

x
Quit, discarding changes

= / ***** First / last message

Tab
Next new or unread message

J / **K**
Next / previous message in the pager

READING

h Show with all headers

T / **S**
Toggle / skip quoted text

a
Create alias from sender

v
Show MIME parts (attachments)

WRITE AND REPLY

m
Compose a new message

r Reply to sender

g Reply to all

L Reply to mailing list

f Forward with comments

WRITE AND REPLY (cont.)

y
Send the message (in compose)

t / **c** / **b** / **s**
Edit To / Cc / Bcc / Subject

e / **E**
Edit body / body with headers

a / **A** / **D**
Attach file / message / remove

DELETE AND TAG

d Mark message deleted

u Undelete the message

$
Apply changes to the folder

t Tag the message

;
Apply next key to tagged messages

THREADS

Ctrl + **N** / **Ctrl** + **P**
Next / previous thread

Esc › **v**
Collapse or expand this thread

THREADS (cont.)

Esc › **V**
Collapse or expand all threads

P
Jump to parent message

SEARCH AND LIMIT

/ Search forward

Esc › **/** Search backward

n Next search match

l Limit view to a pattern

FOLDERS AND SAVING

c Change folder

.
List mailboxes with new mail

s
Save (move) message to a folder

ATTACHMENTS

Enter / **m** / **T**
View attachment / via mailcap / as text

s / **p**
Save / print attachment

COMMAND LINE

`neomutt`
Open the default mailbox

`neomutt -f <file>`
Open a given mailbox or folder

`neomutt -R`
Open read-only

`neomutt -Z`
Open first mailbox with new mail, else exit

`neomutt -s "<subj>" <addr>`
Compose and send a message

`neomutt -a <file> -- <addr>`
Send with an attachment

`neomutt -c <addr>`
Add a Cc recipient

RECIPES

Send a file from a script

```
echo "Attached" | neomutt \
  -s "Report" -a r.pdf --
bob@example.org
```

HELP

?
Show key list for this screen

`man neomutt`
Manual page