NeoMutt Terminal email client

Index message list → `Enter` **Pager** read one mail → `r` / `m` **Compose** headers, attach → `y` **Sent** back to index

CONCEPTS

Keys depend on the screen: the index lists mail, the pager shows one message, compose edits one. Press ? on any screen for its live key list.

Deletes and flag changes are only marked until you sync with $ or leave the folder; u undeletes before that.

Esc in a key means Alt (or press Esc first). Defaults can differ: your config may rebind keys, so check ? first.

MOVING AROUND

`j` / `k`
Next / previous message

`Enter` Open the message

`Space`
Page down, then next message

`-` / `Backspace`
Page up / line up in the pager

`q`
Leave pager or folder, then quit

MOVING AROUND (cont.)

`x`
Quit, discarding changes

`=` / `*` First / last message

`Tab`
Next new or unread message

`J` / `K`
Next / previous message in the pager

READING

`h` Show with all headers

`T` / `S`
Toggle / skip quoted text

`a`
Create alias from sender

`v`
Show MIME parts (attachments)

WRITE AND REPLY

`m`
Compose a new message

`r` Reply to sender

`g` Reply to all

`L` Reply to mailing list

`f` Forward with comments

WRITE AND REPLY (cont.)

`y`
Send the message (in compose)

`t` / `c` / `b` / `s`
Edit To / Cc / Bcc / Subject

`e` / `E`
Edit body / body with headers

`a` / `A` / `D`
Attach file / message / remove

DELETE AND TAG

`d` Mark message deleted

`u` Undelete the message

`$`
Apply changes to the folder

`t` Tag the message

`;`
Apply next key to tagged messages

THREADS

`Ctrl` + `N` / `Ctrl` + `P`
Next / previous thread

`Esc` › `v`
Collapse or expand this thread

THREADS (cont.)

`Esc` › `V`
Collapse or expand all threads

`P`
Jump to parent message

SEARCH AND LIMIT

`/` Search forward

`Esc` › `/` Search backward

`n` Next search match

`l` Limit view to a pattern

FOLDERS AND SAVING

`c` Change folder

`.`
List mailboxes with new mail

`s`
Save (move) message to a folder

ATTACHMENTS

`Enter` / `m` / `T`
View attachment / via mailcap / as text

`s` / `p`
Save / print attachment

COMMAND LINE

`neomutt`
Open the default mailbox

`neomutt -f <file>`
Open a given mailbox or folder

`neomutt -R`
Open read-only

`neomutt -Z`
Open first mailbox with new mail, else exit

`neomutt -s "<subj>" <addr>`
Compose and send a message

`neomutt -a <file> -- <addr>`
Send with an attachment

`neomutt -c <addr>`
Add a Cc recipient

RECIPES

Send a file from a script

```
echo "Attached" | neomutt \
  -s "Report" -a r.pdf --
bob@example.org
```

HELP

`?`
Show key list for this screen

`man neomutt`
Manual page