nerdctl Docker-like CLI for containerd

START HERE

`nerdctl run -d -p <host>:<ctr> <image>`
Start a container

`nerdctl build -t <name> .`
Build an image

`nerdctl ps`
List running containers

`nerdctl compose up -d`
Start a Compose stack

`nerdctl logs -f <container>`
Follow output

`nerdctl --namespace k8s.io ps`
See Kubernetes containers

`nerdctl exec -it <container> sh`
Shell in a container

`nerdctl system prune -a`
Clean up unused data

nerdctl CLI → gRPC → **containerd** images, namespaces → shim → **runc** OCI runtime → starts → **Container** CNI network

CONCEPTS

nerdctl is a Docker-compatible CLI that talks straight to containerd. Most docker commands and flags work unchanged; flags that are not implemented yet are rejected.

Containers and images live in a containerd namespace (default: default). Kubernetes uses k8s.io, so pass --namespace k8s.io to see its containers.

nerdctl build needs a running buildkitd. Rootless use needs a separate rootless containerd setup (see the rootless docs).

RUN

`nerdctl run <image>`
Create and start a container

`nerdctl run -d <image>`
Run in the background

`nerdctl run -it <image> sh`
Interactive shell

`nerdctl run --rm <image>`
Delete the container on exit

`nerdctl run --name <name> <image>`
Give the container a name

`nerdctl run -p <host>:<ctr> <image>`
Publish a port

Format is [HOST_IP:]HOST_PORT:CONTAINER_PORT[/PROTO].

`nerdctl run -v <name>:<path> <image>`
Mount a named volume

`nerdctl run -v <dir>:<path>:ro <image>`
Bind-mount read-only

`nerdctl run -e KEY=VALUE <image>`
Set an environment variable

`nerdctl run --env-file <file> <image>`
Load variables from a file

`nerdctl run --net <network> <image>`
Join a network

May be given more than once to join several networks.

RUN (cont.)

`nerdctl run --restart unless-stopped <image>`
Restart after crashes and reboots

`nerdctl create <image>`
Create without starting

CONTAINERS

`nerdctl ps`
List running containers

`nerdctl ps -a`
List all, including stopped

`nerdctl stop <container>`
Stop gracefully

`nerdctl start <container>`
Start a stopped container

`nerdctl restart <container>`
Stop and start again

`nerdctl rm <container>`
Remove a stopped container

`nerdctl rm -f <container>`
Force-remove a running one

`nerdctl ps -q`
Print only container IDs

`nerdctl ps -f status=exited`
Filter the list

`nerdctl stats --no-stream`
One-shot CPU and memory usage

INSIDE A CONTAINER

`nerdctl exec -it <container> sh`
Open a shell in a running container

`nerdctl exec <container> <cmd>`
Run one command

`nerdctl logs <container>`
Show output

Only containers started with run -d are supported.

`nerdctl logs -f <container>`
Follow output live

`nerdctl logs -n <lines> <container>`
Only the last lines

`nerdctl logs --since <duration> <container>`
Only recent output, e.g. 10m

`nerdctl cp <container>:<path> <dest>`
Copy out of a container

Use only with trusted containers.

INSIDE A CONTAINER (cont.)

`nerdctl cp <src> <container>:<path>`
Copy into a container

`nerdctl inspect <object>`
Low-level details as JSON

IMAGES

`nerdctl pull <image>`
Download an image

`nerdctl images`
List local images

`nerdctl build -t <name> .`
Build from a Dockerfile here

`nerdctl build -f <file> -t <name> .`
Use another Dockerfile

`nerdctl build --build-arg KEY=VALUE .`
Pass a build variable

`nerdctl build --no-cache .`
Ignore the build cache

`nerdctl tag <image> <repo>:<tag>`
Add a name to an image

`nerdctl push <repo>:<tag>`
Upload to a registry

`nerdctl login <registry>`
Log in to a registry

Use --password-stdin in scripts.

`nerdctl rmi <image>`
Remove an image

`nerdctl save -o <file> <image>`
Export an image to a tar file

`nerdctl load -i <file>`
Import an image from a tar file

`nerdctl image prune -a`
Remove unused images

`nerdctl pull --platform <os/arch> <image>`
Pull another platform

VOLUMES AND NETWORKS

`nerdctl volume create <name>`
Create a named volume

`nerdctl volume ls`
List volumes

`nerdctl volume rm <name>`
Remove a volume

`nerdctl volume prune`
Remove unused volumes

VOLUMES AND NETWORKS (cont.)

`nerdctl network create <name>`
Create a bridge network

`nerdctl network ls`
List networks

COMPOSE

`nerdctl compose up -d`
Create and start the stack

`nerdctl compose down`
Stop and remove containers and networks

`nerdctl compose ps`
List the stack's containers

`nerdctl compose logs -f <service>`
Follow service logs

`nerdctl compose exec <service> sh`
Shell in a service

`nerdctl compose up --build`
Rebuild images, then start

`nerdctl compose build`
Build service images

`nerdctl compose pull`
Pull service images

`nerdctl compose stop`
Stop without removing

`nerdctl compose down -v`
Also remove volumes

Deletes named volumes declared in the file: data is lost.

`nerdctl compose config`
Show the resolved file

NAMESPACES AND DAEMON

`nerdctl --namespace <ns> <cmd>`
Run against a containerd namespace

Containers and images are per namespace; k8s.io holds Kubernetes workloads.

`nerdctl namespace ls`
List namespaces

`nerdctl --address <socket> <cmd>`
Use another containerd socket

`nerdctl system df`
Show disk usage

`nerdctl system prune`
Remove stopped containers and dangling data