# Newsboat Terminal RSS reader

## CONCEPTS

> Lower-case letters are plain keys; Shift+<letter> is the upper-case key. The same key can do different things in each view; ? shows the keys of the current one.

## FEED LIST

**Enter**
Open the feed's article list

**Shift** + **R**
Reload all feeds

**r**
Reload the selected feed

**Shift** + **A**
Mark selected feed as read

**Shift** + **C**
Mark all feeds as read

**Shift** + **Q**
Quit from any view

## ARTICLE LIST

**n** / **p**
Next / previous unread article

**o**
Open in browser

**Shift** + **O**
Open in browser, mark read

**Shift** + **N**
Toggle read / unread

## ARTICLE VIEW

**1-9**
Open link 1 to 9 in browser

**u**
List the article's URLs

**Space** / **b**
Page down / up

## LISTS AND DIALOGS

**Arrows**
Move in lists

**PageUp** / **PageDown**
Move one page

**g**
Sort by chosen method

**?**
Show the help screen

## SEARCH AND FILTER

**/**
Search feeds or articles

**f**
Pick a saved filter

**Shift** + **F**
Type a filter expression

**t**
Select a tag

### Filter expressions

| Write | Matches |
|---|---|
| `unread_count > 0` | feeds with unread items |
| `title =~ "linux"` | regex, case-insensitive |
| `author =! "bob"` | not equal |
| `age between 0:7` | published in last 7 days |
| `tags # "news"` | word in a list |
| `a and (b or c)` | combine, group |

## CONFIG AND CLI

**`newsboat -r`**
Start and reload all feeds

### Common config options

| Option | Effect |
|---|---|
| `browser` | program for links |
| `reload-time` | minutes between reloads |
| `auto-reload` | reload while running |
| `show-read-feeds` | hide read feeds if no |
| `bind-key` | rebind a key |
| `unbind-key` | free a key |
| `macro` | chain operations |