Ninja Fast build executor

START HERE

`cmake -G Ninja -B build`
Generate a build.ninja

`ninja -C build`
Build the default targets

`ninja -C build <target>`
Build one target

`ninja -n -v`
Preview the commands

`ninja -k 0`
Keep going past failures

`ninja -j <N>`
Set parallel jobs

`ninja -t targets all`
List what can be built

`ninja -t clean`
Remove built files

CMakeLists / meson.build you write → **`cmake / meson setup`** → **build.ninja** generated → **`ninja`** → **Outputs** only what is stale

CONCEPTS

Ninja is a fast executor, not a build language: a generator such as CMake or Meson writes build.ninja for you.

Ninja skips the work when outputs are newer than their inputs and the recorded command is unchanged.

Do not hand-edit generated build.ninja; change the generator input and it regenerates itself.

BUILDING

`ninja`
Build the default targets

`ninja <target>`
Build only the named target(s)

`ninja -C <dir>`
Change to a directory first
Typical out-of-source use: ninja -C build.

`ninja -j <N>`
Run N jobs in parallel
0 means unlimited; the default follows the CPU count.

`ninja -n`
Dry run, do not execute

`ninja -v`
Show full command lines

`ninja -k <N>`
Keep going until N jobs fail
0 means never stop; default is 1.

`ninja -f <file>`
Use another build file

`ninja -l <N>`
Hold back at load average above N

`ninja --quiet`
Hide progress, show command output

`ninja --version`
Print the Ninja version

`ninja -h`
Show help and options

INSPECTING THE GRAPH

`ninja -t targets all`
List every target and its rule

INSPECTING THE GRAPH (cont.)

`ninja -t targets rule <rule>`
List targets built by a rule

`ninja -t targets depth <n>`
List targets down to a depth

`ninja -t commands <target>`
Print commands to rebuild a target

`ninja -t query <path>`
Show a file's inputs and outputs

`ninja -t inputs <target>`
List all inputs of a target

`ninja -t graph <target>`
Emit a Graphviz dot file

`ninja -t rules`
List all rules

`ninja -t deps <target>`
Show deps recorded from depfiles

`ninja -t missingdeps`
Find missing generated-file deps

`ninja -t browse <target>`
Browse the graph in a browser
Needs Python; --port and --no-browser are available.

`ninja -t multi-inputs <target>`
Map targets to their inputs

`ninja -t list`
List all subtools

CLEANING AND TOOLING

`ninja -t clean`
Remove all built files

`ninja -t clean <target>`
Clean one target and its deps

`ninja -t clean -r <rule>`
Clean outputs of a rule

`ninja -t clean -g`
Also remove generated files

`ninja -t cleandead`
Remove outputs no longer in manifest

`ninja -t compdb <rule> ...`
Dump compile_commands.json
Redirect to a file: ninja -t compdb cc > compile_commands.json (rule names depend on the generator).

CLEANING AND TOOLING (cont.)

`ninja -t compdb-targets <target>`
Compdb limited to given targets

`ninja -t recompact`
Compact the deps and build logs

`ninja -t restat`
Re-stat outputs in the build log

DEBUGGING AND ENV

`ninja -d explain`
Say why each command reruns

`ninja -d stats`
Print operation counts and timing

`ninja -d keepdepfile`
Keep depfiles after reading

`ninja -d keeprsp`
Keep response files on success

`ninja -d list`
List debug modes

`ninja -w list`
List warning flags

`NINJA_STATUS="[%f/%t %e] " ninja`
Customize progress line
%f finished, %t total, %p percent, %e elapsed seconds.

`ninja -j1 -v`
Serial verbose build to find a failure

WRITING BUILD.NINJA

`rule <name>`
Declare a rule with a command
Indented lines set command, description, depfile, deps.

`command = cc -c $in -o $out`
Rule command using $in and $out

`build <out>: <rule> <in>`
Declare a build edge

`build <out>: <rule> <in> | <dep>`
Add an implicit dependency

`build <out>: <rule> <in> || <dep>`
Add an order-only dependency

`default <target>`
Set what a bare ninja builds

WRITING BUILD.NINJA (cont.)

`build <name>: phony <targets>`
Alias for other targets

`depfile = $out.d`
Read header deps from a depfile

`deps = gcc`
Store depfile deps in the deps log

`description = CC $out`
Short text shown while building

`pool <name>`
Declare a pool, set depth to cap jobs

`restat = 1`
Skip dependents if output is unchanged

`generator = 1`
Mark a rule as the regenerator

`include <file>`
Include a file in the same scope

`subninja <file>`
Include a file in a new scope

`ninja_required_version = 1.10`
Require a minimum Ninja

`builddir = <dir>`
Directory for .ninja_log and deps log

RECIPES

Minimal hand-written build

```
rule cc
  command = cc -c $in -o $out
  depfile = $out.d
  deps = gcc
  description = CC $out
rule link
  command = cc $in -o $out
build main.o: cc main.c
build app: link main.o
default app
```

Meson or CMake out-of-tree

```
meson setup build && ninja -C
build
# or
cmake -G Ninja -S . -B build
ninja -C build
```

Compilation database for clangd

```
ninja -C build -t compdb cc cxx
> compile_commands.json
```

Find why it rebuilds

```
ninja -d explain -n
ninja -t query <path>
```