Ninja Fast build executor

CONCEPTS

Ninja is a fast executor, not a build language: a generator such as CMake or Meson writes build.ninja for you.

CMakeLists / meson.build you write
↓ cmake / meson setup
build.ninja generated
↓ ninja
Outputs only what is stale

Ninja skips the work when outputs are newer than their inputs and the recorded command is unchanged.

Do not hand-edit generated build.ninja; change the generator input and it regenerates itself.

BUILDING

ninja
Build the default targets

ninja *<target>*
Build only the named target(s)

ninja -C *<dir>*
Change to a directory first

ninja -j *<N>*
Run N jobs in parallel

ninja -n
Dry run, do not execute

ninja -v
Show full command lines

ninja -k *<N>*
Keep going until N jobs fail

ninja -f *<file>*
Use another build file

ninja -l *<N>*
Hold back at load average above N

ninja --quiet
Hide progress, show command output

ninja --version
Print the Ninja version

ninja -h
Show help and options

INSPECTING THE GRAPH

ninja -t targets all
List every target and its rule

ninja -t targets rule *<rule>*
List targets built by a rule

ninja -t targets depth *<n>*
List targets down to a depth

ninja -t commands *<target>*
Print commands to rebuild a target

ninja -t query *<path>*
Show a file's inputs and outputs

ninja -t inputs *<target>*
List all inputs of a target

ninja -t graph *<target>*
Emit a Graphviz dot file

ninja -t rules
List all rules

ninja -t deps *<target>*
Show deps recorded from depfiles

ninja -t missingdeps
Find missing generated-file deps

ninja -t browse *<target>*
Browse the graph in a browser

CLEANING AND TOOLING

ninja -t clean
Remove all built files

ninja -t clean *<target>*
Clean one target and its deps

ninja -t clean -r *<rule>*
Clean outputs of a rule

ninja -t compdb *<rule>* **...**
Dump compile_commands.json

DEBUGGING AND ENV

ninja -d explain
Say why each command reruns

ninja -d stats
Print operation counts and timing

NINJA_STATUS="[%f/%t %e] " ninja
Customize progress line

ninja -j1 -v
Serial verbose build to find a failure

WRITING BUILD.NINJA

rule *<name>*
Declare a rule with a command

command = cc -c $in -o $out
Rule command using $in and $out

build *<out>*: *<rule>* *<in>*
Declare a build edge

build *<out>*: *<rule>* *<in>* **|** *<dep>*
Add an implicit dependency

build *<out>*: *<rule>* *<in>* **||** *<dep>*
Add an order-only dependency

default *<target>*
Set what a bare ninja builds

build *<name>*: **phony** *<targets>*
Alias for other targets

depfile = $out.d
Read header deps from a depfile

deps = gcc
Store depfile deps in the deps log

description = CC $out
Short text shown while building

pool *<name>*
Declare a pool, set depth to cap jobs

RECIPES

Minimal hand-written build

```
rule cc
  command = cc -c $in -o $out
  depfile = $out.d
  deps = gcc
  description = CC $out
rule link
  command = cc $in -o $out
build main.o: cc main.c
build app: link main.o
default app
```

Meson or CMake out-of-tree

```
meson setup build && ninja -C
build
# or
cmake -G Ninja -S . -B build
ninja -C build
```

Compilation database for clangd

```
ninja -C build -t compdb cc cxx >
compile_commands.json
```

Find why it rebuilds

```
ninja -d explain -n
ninja -t query <path>
```