Node.js JavaScript runtime CLI

CONCEPTS

node runs a file as a CommonJS script, or as an ES module for .mjs, "type": "module" or --input-type=module.

NODE_OPTIONS environment defaults
↓ then
Node flags node --watch ...
↓ then
Script file.js or -e
↓ gets
Arguments process.argv

Flags go before the script name; everything after it is passed to the script. Use -- to end node's own options.

RUN CODE

`node <file>`
Run a script

`node`
Start the interactive REPL

`node -e "<code>"`
Evaluate a string of code

`node -p "<expr>"`
Evaluate and print the result

`node <file> <args>`
Pass arguments to the script

`node -`
Read the script from stdin

`node -c <file>`
Syntax check without running

`node --input-type=module -e "<code>"`
Evaluate code as an ES module

`node -v`
Print the Node version

`corepack enable`
Activate pnpm and yarn shims

WATCH MODE

`node --watch <file>`
Restart when imported files change

`node --watch-path=<dir> <file>`
Watch specific paths instead

WATCH MODE (cont.)

`node --watch-preserve-output <file>`
Keep the console between restarts

TEST RUNNER

`node --test`
Run all discovered test files

`node --test <file>`
Run specific test files

`node --test-name-pattern="<regex>"`
Run tests whose name matches

`node --test-only`
Run only tests marked only

`node --test-reporter=<name>`
Choose output: spec, tap, dot, junit

`node --test --watch`
Re-run tests on change

ENVIRONMENT AND CONFIG

`node --env-file=<file> <script>`
Load variables from a .env file

`NODE_OPTIONS="<flags>" node <script>`
Set default flags via environment

`NODE_ENV=production node <script>`
Set a variable for one run

`node --run <script>`
Run a package.json script

DEBUGGING

`node --inspect <file>`
Start with the inspector open

`node --inspect-brk <file>`
Break on the first line

`node inspect <file>`
Use the built-in CLI debugger

`node --enable-source-maps <file>`
Map stack traces to source files

`node --trace-warnings <file>`
Show where warnings come from

DEBUGGING (cont.)

`node --no-warnings <file>`
Silence all process warnings

PERFORMANCE AND MEMORY

`node --max-old-space-size=<MiB> <file>`
Raise the heap limit

PERMISSIONS AND TYPESCRIPT

`node --permission --allow-fs-read=<path> <file>`
Restrict file access

`node <file>.ts`
Run TypeScript by stripping types

REPL

Dot commands

Command	Effect
`.help`	List commands
`.editor`	Multi-line editor, Ctrl+D runs
`.load <file>`	Run a file in the session
`.save <file>`	Save the session to a file
`.break`	Abandon a multi-line input
`.exit`	Leave (or Ctrl+D)

`Tab`
Complete names and properties

`_`
Last evaluated result

Core modules like fs and path are available in the REPL and in -p/-e without require.

RECIPES

One-liners

```
# random UUID
node -p "crypto.randomUUID()"
# today as ISO date
node -p "new Date().toISOString()"
# usable CPU count
node -p
"os.availableParallelism()"
```

Dev loop with env and watch

```
node --watch --env-file=.env
server.js
# tests alongside
node --test --watch
```