Nox Python session runner

noxfile.py @nox.session → `nox -s` → **Virtualenv** .nox/<name> → `session.install` → **Dependencies** pip / uv → `session.run` → **Commands** tests, lint, docs

CONCEPTS

Sessions are plain Python functions in noxfile.py; each gets its own fresh virtualenv under .nox/.

Without -s, every session in nox.options.sessions (or all, if unset) runs in file order.

RUNNING

`nox`
Run all default sessions

`nox -s <session> [<session>...]`
Run named sessions

`nox -l`
List sessions and their Pythons

`nox -- <args>`
Pass args to sessions as posargs

`nox -p <version>`
Only sessions using this Python

`nox -f <file>`
Use another noxfile

`nox -t <tag> [<tag>...]`
Run sessions with a tag

`nox -k "<expr>"`
Select by keyword expression

RUNNING (cont.)

`nox -s "tests(dj='5')"`
Run one parametrized variant

`nox -x`
Stop after the first failure

`nox --usage <session>`
Show a session's docstring

`nox -P <version>`
Force this Python for all sessions

`nox --report <file.json>`
Write a JSON result report

`nox -j <N|auto>`
Run sessions in parallel

`nox --error-on-missing-interpreters`
Fail instead of skipping

ENVIRONMENTS & EXECUTION

`nox -r`
Reuse existing virtualenvs

`nox -R`
Reuse venvs and skip installs

`nox --install-only`
Install deps, skip session.run

`nox --no-install`
Skip install calls on reused venv

ENVIRONMENTS & EXECUTION (cont.)

`nox -N`
Undo reuse set in the noxfile

`nox -db uv`
Default venv backend (uv, virtualenv...)

`nox --no-venv`
Run in the current interpreter

NOXFILE

`import nox`
Load the library

`@nox.session`
Define a session function

`@nox.session(python=["3.11", "3.12"])`
Run once per Python

`session.install("<pkg>")`
Install into the session venv

`session.install("-e", ".")`
Install the project editable

`session.run("<cmd>", "<arg>")`
Run a command in the venv

`session.posargs`
Args given after --

`session.run("pytest", *session.posargs)`
Forward posargs to a tool

NOXFILE (cont.)

`@nox.session(name="<name>")`
Set a name different from the function

`@nox.session(tags=["<tag>"])`
Group sessions for -t

`@nox.parametrize("<arg>", [<v1>, <v2>])`
Run once per value

`@nox.session(venv_backend="uv")`
Choose backend per session

`@nox.session(reuse_venv=True)`
Reuse this session's venv

`session.notify("<session>")`
Queue another session after this one

`session.skip("<reason>")`
Skip the session with a message

`session.chdir("<dir>")`
Change directory for later commands

`session.run("<cmd>", external=True)`
Allow a program outside the venv

NOXFILE (cont.)

`session.run(..., env={"K": "V"})`
Set env vars for one command

`session.python`
Python version of this run

`nox.options.sessions = [...]`
Default sessions when none given

`nox.options.default_venv_backend = "uv"`
Set backend for the whole file

RECIPES

Test matrix with uv

```
import nox

nox.options.
default_venv_backend = "uv"

@nox.session(python=["3.11",
"3.12", "3.13"])
def tests(session):
    session.install("-e",
".", "pytest")
    session.run("pytest",
*session.posargs)
```

Fast local loop

```
nox -s tests -p 3.12 -R -- -
x -k parser

# first time: nox -s tests -
p 3.12 -r
```