Nx Monorepo build system

CONCEPTS

A project has targets (build, test, ...). Nx runs a target, replays cached output when inputs are unchanged, and runs dependencies first.

Project graph projects + deps
↓ target deps
Task graph what to run
↓ hash inputs
Cache hit: replay
↓ miss: run
Run parallel

RUN TASKS

`nx run <project>:<target>`
Run one target

`nx <target> <project>`
Shorthand for run

`nx run <p>:<t>:<config>`
Use a configuration

`nx <target> <project> -c <config>`
Set configuration by flag

`nx run-many -t <target>`
Run a target everywhere

`nx run-many -t <t1> <t2>`
Run several targets

`nx run-many -t <target> -p <a> <b>`
Limit to projects

`nx run-many -t <target> -p "tag:<tag>"`
Select projects by tag

`nx affected -t <target>`
Only affected projects

`nx affected -t <target> --base=<ref> --head=<ref>`
Compare two refs

`--parallel=<n>`
Max concurrent tasks (default 3)

`--nxBail`
Stop after first failure

INSPECT

`nx graph`
Open the project graph

`nx show projects`
List projects

`nx show projects --withTarget=<t>`
Projects with a target

`nx show project <project>`
Resolved project config

GENERATE AND SET UP

`nx g <plugin>:<generator> <name>`
Run a generator

`nx g <plugin>:<generator> --dry-run`
Preview file changes

`nx add <package>`
Install and set up a plugin

`nx init`
Add Nx to an existing repo

`nx migrate --runMigrations`
Apply migrations.json

CACHE AND DAEMON

`nx reset`
Clear cache, daemon, graph data

CONFIG FILES

`project.json: targets`
Per-project task definitions

`targets.<t>.dependsOn`
Tasks that run first

`"^build" in dependsOn`
Same target in dependencies

`targets.<t>.outputs`
Paths to cache

`targets.<t>.cache: true`
Make a target cacheable

`nx.json: targetDefaults`
Shared target settings