OpenShift CLI (oc) OpenShift cluster CLI

CONCEPTS

oc contains kubectl: get, describe, apply, logs, exec, scale and every other kubectl verb work unchanged as oc <verb>. This sheet lists only what OpenShift adds.

LOGIN & SESSION

`oc login <url>`
Log in, prompting for credentials

`oc login --token=<token> --server=<url>`
Log in with a token

`oc whoami`
Show logged-in user

`oc logout`
End the session

PROJECTS

`oc projects`
List projects you can access

`oc project`
Show current project

`oc project <name>`
Switch project

`oc new-project <name>`
Create and switch to project

`oc status`
Overview of the current project

APPS & BUILDS

`oc new-app <git-url>`
Detect, build and deploy source

`oc new-app --image=<img> --name=<name>`
Deploy an existing image

`oc new-app <builder>~<git-url>`
Build source with a builder image

`oc start-build <bc>`
Start a build

APPS & BUILDS (cont.)

`oc start-build <bc> --follow`
Start and stream build log

`oc start-build <bc> --from-dir=<dir> --follow`
Build from local files

`oc logs -f bc/<bc>`
Follow latest build log

ROUTES & NETWORK

`oc expose svc/<name>`
Create a route for a service

`oc get routes`
List routes and hosts

DEPLOY & ROLLOUT

`oc rollout status deploy/<name>`
Watch a rollout

`oc rollout restart deploy/<name>`
Restart all pods

`oc rollout undo deploy/<name>`
Roll back one revision

`oc set env deploy/<name> <KEY>=<value>`
Set env var (triggers rollout)

IMAGES

`oc tag <is>:<tag> <is>:<newtag>`
Point a tag at an image

DEBUG & FILES

`oc rsh <pod>`
Shell in first container

`oc debug deploy/<name>`
Copy pod and open a shell

`oc debug node/<node>`
Root shell on a node

ADMIN (OC ADM)

`oc adm must-gather`
Collect cluster data for support