Open Policy Agent

Policy as code

CONCEPTS

OPA evaluates a query against data (policies plus JSON) and an input document; the answer is JSON.

Policy .rego files
↓ opa check / fmt
Tested test_ rules
↓ opa test
Bundle .tar.gz
↓ opa build
Server opa run -s
↓ query
Decision JSON result

Rules are queried as data.<package>.<rule>; an undefined result prints an empty object, not false.

EVAL

`opa eval -d <path> '<query>'`
Evaluate a query against policy and data

`opa eval -d <path> -i <input.json> '<query>'`
Supply an input document

`opa eval -d <path> -I '<query>'`
Read input from stdin

`opa eval -b <bundle> '<query>'`
Load a bundle instead of paths

`opa eval -f pretty '<query>'`
Human-readable output

`opa eval -f raw '<query>'`
Script-friendly value output

`opa eval -f values '<query>'`
One result array per line

`opa eval --fail '<query>'`
Exit non-zero if undefined or empty

`opa eval --fail-defined '<query>'`
Exit non-zero if the result is defined

`opa eval --explain=full '<query>'`
Trace how the query evaluated

REPL AND SERVER

`opa run`
Start the interactive REPL

`opa run <path>`
REPL with policies and data loaded

`opa run -s <path>`
Start the HTTP server

`opa run -s -a <addr>`
Listen on another address

`opa run -s -b <bundle>`
Serve a bundle

`opa run -w <path>`
Reload on file changes

`opa run -s -c <config.yaml>`
Use a config file

The server answers POST /v1/data/<path> with a JSON body of the form {"input": {...}}.

TESTING

`opa test <path>`
Run all test_ rules

`opa test -v <path>`
Verbose, one line per test

`opa test -r '<regex>' <path>`
Run matching tests only

`opa test -c <path>`
Report coverage

`opa test --threshold <pct> -c <path>`
Fail below a coverage percentage

`opa test -w <path>`
Rerun tests on file changes

`opa test -f json <path>`
Machine-readable results

FORMAT AND CHECK

`opa fmt <path>`
Print formatted source

`opa fmt -w <path>`
Rewrite files in place

`opa fmt -d <path>`
Show a diff of changes

`opa fmt -l <path>`
List files that would change

FORMAT AND CHECK (cont.)

`opa fmt --fail <path>`
Exit non-zero if files need formatting

`opa check <path>`
Parse and compile check

`opa check -S <path>`
Strict mode checks

BUNDLES

`opa build <path>`
Build a bundle (bundle.tar.gz)

`opa build -b <dir> -o <file>`
Name the output file

`opa build -r <rev> <path>`
Set the bundle revision

`opa build -e <entrypoint> <path>`
Declare an entrypoint

`opa build -O=1 -e <entrypoint> <path>`
Optimize (needs an entrypoint)

`opa inspect <bundle>`
Summarize a bundle

OTHER COMMANDS

`opa exec -b <bundle> <input.json>`
Run the default decision on input files

`opa version`
Show version and build

Most commands take -d for data/policy paths and -b for bundles; both read directories recursively.

RECIPES

Gate a Kubernetes manifest in CI

```
# deny rule must come back empty
opa eval --fail-defined -d policy/
-i deploy.json 'data.k8s.deny'
```

Check, format and test before commit

```
opa fmt --fail policy/
opa check -S policy/
opa test -c --threshold 80 policy/
```