pandas Python data frames

CONCEPTS

A DataFrame is a set of Series (columns) sharing one index (row labels). Most operations align on that index, not on position.

Read read_csv, read_parquet
↓ inspect
Clean select, astype, fillna
↓ transform
Shape groupby, merge, pivot
↓ export
Write to_parquet, to_csv

Copy-on-Write
pandas 3 uses Copy-on-Write: any derived frame or column acts as a copy. Chained assignment like df["a"][0] = 1 never changes df; use df.loc[0, "a"] = 1.

READ AND WRITE

pd.read_csv("*file*")
Read a CSV file

pd.read_csv("*file*", parse_dates=["*col*"])
Parse a column as dates

pd.read_parquet("*file*")
Read a Parquet file

df.to_csv("*file*", index=False)
Write CSV without the index

df.to_parquet("*file*")
Write Parquet (keeps dtypes)

INSPECT

df.head(*n*) / df.tail(*n*)
First or last rows (default 5)

df.info()
Columns, dtypes, non-null counts

df.describe()
Summary statistics

df.shape
(rows, columns)

df.dtypes
Type of each column

df["*col*"].value_counts()
Count each distinct value

SELECT

df["*col*"]
One column as a Series

df[["*a*", "*b*"]]
Several columns as a DataFrame

df.loc[*rows*, *cols*]
Select by label

df.iloc[*rows*, *cols*]
Select by position

df[df["*col*"] > 0]
Filter rows with a mask

df[(*cond1*) & (*cond2*)]
Combine conditions

df[df["*col*"].isin([...])]
Rows whose value is in a list

CHANGE COLUMNS

df["*new*"] = df["*a*"] * 2
Add or overwrite a column

df.assign(*new*=lambda d: d.*a* + d.*b*)
Add columns, return a new frame

df.loc[*mask*, "*col*"] = *value*
Set values where a condition holds

df.rename(columns={"*old*": "*new*"})
Rename columns

df.drop(columns=["*col*"])
Remove columns

df["*col*"].astype("*dtype*")
Convert type (int64, float, str, category)

MISSING DATA

df.isna().sum()
Count missing values per column

df.dropna()
Drop rows with any missing value

df.fillna(*value*)
Fill missing values

SORT AND DEDUPE

df.sort_values("*col*", ascending=False)
Sort rows by a column

SORT AND DEDUPE (cont.)

df.drop_duplicates(subset=["*col*"])
Drop duplicate rows

df.reset_index(drop=True)
Renumber rows 0..n-1

GROUP AND AGGREGATE

df.groupby("*key*")["*col*"].sum()
Total per group

df.groupby("*key*").agg(*out*=("*col*", "sum"))
Named aggregation

COMBINE

df.merge(*other*, on="*key*")
Join on a column (inner)

df.merge(*other*, on="*key*", how="left")
Left join

pd.concat([*df1*, *df2*], ignore_index=True)
Stack frames vertically

RESHAPE

df.pivot_table(index="*r*", columns="*c*", values="*v*", aggfunc="sum")
Spreadsheet-style pivot

df.melt(id_vars=["*id*"], var_name="*k*", value_name="*v*")
Wide to long

TEXT

df["*col*"].str.contains("*pat*", na=False)
Regex match as a mask

DATES AND TIME SERIES

pd.to_datetime(df["*col*"])
Parse text as datetimes

df["*col*"].dt.year
Date part
(also .month, .day_name())