pandas Python data frames

CONCEPTS

A DataFrame is a set of Series (columns) sharing one index (row labels). Most operations align on that index, not on position.

Read read_csv, read_parquet
↓ inspect
Clean select, astype, fillna
↓ transform
Shape groupby, merge, pivot
↓ export
Write to_parquet, to_csv

Copy-on-Write
pandas 3 uses Copy-on-Write: any derived frame or column acts as a copy. Chained assignment like df["a"][0] = 1 never changes df; use df.loc[0, "a"] = 1.

READ AND WRITE

pd.read_csv("*<file>*")
Read a CSV file

pd.read_parquet("*<file>*")
Read a Parquet file

df.to_csv("*<file>*", index=False)
Write CSV without the index

df.to_parquet("*<file>*")
Write Parquet (keeps dtypes)

INSPECT

df.head(*<n>*) / df.tail(*<n>*)
First or last rows (default 5)

df.info()
Columns, dtypes, non-null counts

df.describe()
Summary statistics

df.shape
(rows, columns)

df["*<col>*"].value_counts()
Count each distinct value

SELECT

df["*<col>*"]
One column as a Series

SELECT (cont.)

df[["*<a>*", "*<b>*"]]
Several columns as a DataFrame

df.loc[*<rows>*, *<cols>*]
Select by label

df.iloc[*<rows>*, *<cols>*]
Select by position

df[df["*<col>*"] > 0]
Filter rows with a mask

df[(*<cond1>*) & (*<cond2>*)]
Combine conditions

df[df["*<col>*"].isin([...])]
Rows whose value is in a list

CHANGE COLUMNS

df["*<new>*"] = df["*<a>*"] * 2
Add or overwrite a column

df.rename(columns={"*<old>*": "*<new>*"})
Rename columns

df.drop(columns=["*<col>*"])
Remove columns

MISSING DATA

df.isna().sum()
Count missing values per column

df.dropna()
Drop rows with any missing value

df.fillna(*<value>*)
Fill missing values

SORT AND DEDUPE

df.sort_values("*<col>*", ascending=False)
Sort rows by a column

GROUP AND AGGREGATE

df.groupby("*<key>*")["*<col>*"].sum()
Total per group

COMBINE

df.merge(*<other>*, on="*<key>*")
Join on a column (inner)

pd.concat([*<df1>*, *<df2>*], ignore_index=True)
Stack frames vertically