GNU Parallel

Parallel shell jobs

CONCEPTS

Think xargs with sane defaults: one job per argument, one job per CPU thread, and output of each job never interleaved.

Input ::: / :::: / stdin
↓ split
Arguments one per job
↓ fill {}
Job slots -j N at a time
↓ group
Output per job, in order with -k

Several ::: groups give every combination; use :::+ to pair them up instead.

INPUTS

parallel *<cmd>* **:::** *<a>* *<b>* *<c>*
Arguments on the command line

<producer> **| parallel** *<cmd>*
One argument per stdin line

parallel *<cmd>* **::::** *<file>*
One argument per line of a file

parallel -0 *<cmd>*
NUL-separated stdin (find -print0)

parallel *<cmd>* **:::** *<a>* *<b>* **:::** *<x>* *<y>*
All combinations of two sources

parallel *<cmd>* **:::** *<a>* *<b>* **:::+** *<x>* *<y>*
Pair sources (a-x, b-y)

REPLACEMENT STRINGS

{}
The argument itself

{.}
Argument without extension

{/}
Basename (no directory)

{/.}
Basename without extension

{#}
Job sequence number

{%}
Job slot number, 1 to -j

RUNNING JOBS

parallel -j *<N>* **...**
Run N jobs at once

parallel -n *<N>* **...**
Up to N arguments per command

SAFETY AND PREVIEW

parallel --dry-run *<cmd>* **:::** *<a>* *<b>*
Print commands, run nothing

parallel --halt now,fail=1 ...
Stop all jobs at first failure

Pipes, redirects and && inside the command need single quotes around the whole command: parallel 'a {} | b > {.}.out' ::: ...

Shell functions need export -f <fn> in bash; aliases and zsh/fish functions need env_parallel.

OUTPUT AND PROGRESS

parallel -k ...
Print output in input order

parallel --bar ...
Progress bar on stderr

parallel --tag ...
Prefix each line with its argument

JOBLOG AND RESUME

parallel --joblog *<file>* **...**
Record seq, time, exit code, command

parallel --joblog *<file>* **--resume ...**
Skip jobs already logged

parallel --joblog *<file>* **--resume-failed ...**
Rerun failed jobs, then the rest

SPLITTING STDIN

<producer> **| parallel --pipe** *<cmd>*
Give each job a block of stdin

REMOTE HOSTS

parallel -S *<host1>*,*<host2>* **...**
Run jobs on these ssh hosts