Parcel Zero-config bundler

Entry index.html or source field → `parcel` → **Dev server** localhost:1234, HMR → `parcel build` → **dist/** minified, hashed files → `parcel watch` → **Watch** rebuild, no HTTP server

CONCEPTS

Zero config: point Parcel at an entry (usually an HTML file) and it follows script, style and image references itself. serve is the default command.

The cache lives in .parcel-cache; add it and dist to .gitignore. When output looks stale or odd, delete the cache or pass --no-cache.

DEV SERVER

`parcel <entry>`
Start the dev server (same as parcel serve)

`parcel serve <entry>`
Explicit form of the dev server

`parcel --port <port>`
Set the port (default 1234 or $PORT)

`parcel --host <host>`
Listen on one host instead of all

`parcel --open [browser]`
Open the entry in a browser

`parcel --https`
Serve dev and HMR over HTTPS

DEV SERVER (cont.)

`parcel --no-hmr`
Turn off hot reloading

`parcel --lazy`
Build only bundles the browser requests

`parcel --hmr-port <port>`
Run the HMR socket on another port

WATCH

`parcel watch <entry>`
Rebuild on change, no HTTP server

BUILD

`parcel build <entry>`
One production build, then exit

`parcel build 'src/*.html'`
Build many entries by glob (quote it)

`parcel build`
Use the source field of package.json

`parcel build --no-optimize`
Skip minification and optimizations

`parcel build --no-scope-hoist`
Disable scope hoisting

BUILD (cont.)

`parcel build --no-content-hash`
Keep names free of content hashes

`parcel build --detailed-report [n]`
List the n largest assets per bundle

`parcel build --no-source-maps`
Do not emit source maps

OUTPUT AND TARGETS

`--dist-dir <dir>`
Output folder (default dist)

`--public-url <url>`
Prefix for absolute URLs in output

`--target <name>`
Build only the named target

package.json fields

Field	Purpose
`source`	Default entry file(s)
`main`	Library output path (CommonJS)
`module`	Library output path (ES module)
`browserslist`	Browsers to support
`targets`	Per-target dist, publicUrl, options

OUTPUT AND TARGETS (cont.)

--dist-dir and --public-url only apply where a target does not set its own distDir or publicUrl.

CACHE AND DIAGNOSTICS

`--no-cache`
Do not read from the cache

`--cache-dir <path>`
Move the cache (default .parcel-cache)

`--log-level <level>`
none, error, warn, info or verbose

`--config <path>`
Use another Parcel config or package

`parcel --version`
Print the Parcel version

CONFIG FILES

Minimal .parcelrc

```
{
  "extends": "@parcel/config-default",
  "transformers": { "*.svg": ["@parcel/transformer-svg-react"] }
}
```

CONFIG FILES (cont.)

Targets in package.json

```
"source": "src/index.html",
"targets": {
  "default": { "distDir": "./public", "publicUrl": "/app" }
}
```

RECIPES

Scripts in package.json

```
"scripts": {
  "start": "parcel src/index.html",
  "build": "parcel build src/index.html"
}
```

Static site for a sub-path

```
rm -rf dist .parcel-cache
npx parcel build src/index.html \
  --public-url /docs/ --dist-dir site
```

Library build with watch

```
# package.json: "source", "main", "module"
npx parcel watch
npx parcel build --no-optimize
```

Test on a phone over HTTPS

```
npx parcel src/index.html --https --host 0.0.0.0
```