pgcli Smarter Postgres shell

CONCEPTS

pgcli is psql with context-aware completion and syntax colours. By default a query runs on Enter after the closing semicolon; F3 switches to multi-line mode.

CONNECT

pgcli -h *<host>* **-p** *<port>* **-U** *<user>* **-d** *<db>*
Connect with explicit options

pgcli *<db>*
Connect to a local database

pgcli "postgresql://*<user>***@***<host>***:***<port>***/***<db>***"**
Connect with a URI

pgcli -D *<alias>*
Connect via a DSN alias from the config

\c *<db>*
Switch database

INSPECT

\l
List databases

\dt
List tables

\d *<table>*
Columns, indexes and constraints

\dn
List schemas

RUN SQL

pgcli -c "*<sql>***"** *<db>*
Run a statement and exit

pgcli -f *<file.sql>* *<db>*
Run a script file and exit

\i *<file>*
Run a file inside pgcli

\e
Edit the query in your editor

RUN SQL (cont.)

\copy *<table>* **from '***<file>***' csv header**
Load a CSV file

\copy (*<query>***) to '***<file>***' csv header**
Export a query to CSV

\?
List all backslash commands

OUTPUT

\x
Toggle vertical output

pgcli --auto-vertical-output
Vertical only when too wide

\timing
Toggle query timing

\T *<format>*
Change the table format

COMPLETION & KEYS

F2
Toggle smart completion

F3
Toggle multi-line mode

F5
Toggle explain mode

Tab
Force completion at the cursor

\refresh
Reload completion metadata

NAMED QUERIES

\ns *<name>* *<query>*
Save a named query

\n *<name>* **[args]**
Run a named query

CONFIG

~/.config/pgcli/config
Main config file