pg_dump and pg_restore


PostgreSQL backups

CONCEPTS

pg_dump saves one database; roles and tablespaces live cluster-wide, so add pg_dumpall -g.

Pick a format (-F)

Flag	Format	Restore with	Parallel -j
`-Fp`	plain SQL (default)	psql	no
`-Fc`	custom archive	pg_restore	restore only
`-Fd`	directory	pg_restore	dump and restore
`-Ft`	tar	pg_restore	no



Dumps are consistent snapshots and do not block writers, so you can dump a live database.

DUMP A DATABASE

`pg_dump <db> > db.sql`
Plain SQL script to stdout

`pg_dump -f db.sql <db>`
Write the script to a file

`pg_dump -Fc -f <file> <db>`
Custom-format archive

`pg_dump -Fd -f <dir> <db>`
Directory-format archive

`pg_dump -Fd -j <n> -f <dir> <db>`
Dump n tables in parallel

CHOOSE WHAT TO DUMP

`pg_dump -s <db>`
Schema only, no data

`pg_dump -a <db>`
Data only, no schema

`pg_dump -t <table> <db>`
Only matching tables

`pg_dump -T <table> <db>`
Skip matching tables

CHOOSE WHAT TO DUMP (cont.)

`pg_dump -n <schema> <db>`
Only matching schemas

`pg_dump -N <schema> <db>`
Skip matching schemas

`pg_dump --no-owner --no-privileges <db>`
Omit owners and GRANTs

RESTORE A DUMP

`psql -X -d <db> -f db.sql`
Restore a plain SQL dump

`pg_restore -d <db> <file>`
Restore an archive into a database

`pg_restore -l <file>`
List the archive's contents

`pg_restore -j <n> -d <db> <file>`
Restore with n parallel jobs

`createdb -T template0 <db>`
Create an empty target first

`pg_restore -C -d postgres <file>`
Create the database from the archive

`pg_restore -c --if-exists -d <db> <file>`
Drop objects before recreating

`pg_restore -s -d <db> <file>`
Schema only

`pg_restore -t <table> -d <db> <file>`
Restore a single table

WHOLE CLUSTER

`pg_dumpall > all.sql`
Every database, roles, tablespaces

`pg_dumpall -g > globals.sql`
Roles and tablespaces only

CONNECTION

`pg_dump -h <host> -p <port> -U <user> <db>`
Connect to another server

pg_restore does not read PGDATABASE. Without -d it prints SQL instead of restoring.