Prettier Opinionated formatter

CONCEPTS

Without --write or --check, Prettier prints the formatted code to stdout and touches nothing.

Parse source to AST
↓ discard layout
Reprint printWidth rules
↓ write / check
Output stdout, file or exit code

Prettier is opinionated: few options, and it reprints from the AST, so your original line breaks mostly do not survive.

Config lookup goes up the tree from each file; there is no global config. CLI flags override the file by default.

RUN

prettier --write *<path>*
Format files in place

prettier --check *<path>*
Report unformatted files, exit 1

prettier --list-different *<path>*
Print names of differing files

prettier *<file>*
Print formatted result to stdout

prettier --ignore-unknown --write .
Skip file types it cannot parse

prettier --no-error-on-unmatched-pattern *<glob>*
No error when nothing matches

prettier --log-level silent *<path>*
Quieter or louder output

prettier --debug-check *<file>*
Test that formatting is safe

INPUT

prettier --stdin-filepath *<path>*
Pick parser and config from a name

INPUT (cont.)

prettier --parser *<name>*
Force a parser (babel, ts, json, md...)

prettier --range-start *<n>* **--range-end** *<n>*
Format only a character range

prettier --require-pragma *<path>*
Only format files with the pragma

COMMON OPTIONS

--print-width *<n>*
Line length to wrap at (80)

--tab-width *<n>*
Spaces per indent level (2)

--use-tabs
Indent with tabs

--no-semi
Omit semicolons

--single-quote
Single quotes in JS/TS

--trailing-comma *<all|es5|none>*
Trailing commas (default all)

--prose-wrap *<always|never|preserve>*
Wrap Markdown text

--end-of-line *<lf|crlf|cr|auto>*
Line ending style (lf)

--arrow-parens *<always|avoid>*
Parens around lone arrow param

--quote-props *<as-needed|consistent|preserve>*
Quote object keys

CONFIGURATION

prettier --config *<file>* *<path>*
Use a specific config file

prettier --no-config *<path>*
Ignore config files, use defaults

prettier --find-config-path *<file>*
Show which config applies

package.json "prettier" key
Config inside package.json

CONFIGURATION (cont.)

.prettierrc / .prettierrc.json
JSON or YAML options file

prettier.config.js / .mjs / .ts
Config as code, export default

"overrides": [{ "files", "options" }]
Per-glob options

IGNORING

.prettierignore
Gitignore syntax, project root

prettier --ignore-path *<file>*
Use another ignore file

// prettier-ignore
Skip next JS/TS node

<!-- prettier-ignore -->
Skip next HTML or Markdown block

node_modules and VCS folders are skipped by default, and .gitignore is honoured.

CACHE AND CI

prettier --cache --write .
Only reformat changed files

Exit codes: 0 all formatted, 1 some files unformatted, 2 Prettier error. Use --check in CI.

RECIPES

CI gate

```
# fails the job on any unformatted file
npx prettier --check .
```

Format only staged files

```
git diff --name-only --cached --diff-filter=d -z \
  | xargs -0 prettier --write --ignore-unknown
git add -u
```

Minimal .prettierrc

```
{
  "singleQuote": true,
  "printWidth": 100,
  "overrides": [{ "files": "*.md", "options": { "proseWrap": "always" } }]
}
```