promtool Prometheus CLI toolkit

START HERE

`promtool check config prometheus.yml`
Validate config and rule files

`promtool check rules <rules.yml>`
Validate alerting and recording rules

`promtool test rules <tests.yml>`
Unit-test rules

`promtool query instant <url> '<expr>'`
Run a query now

`promtool query range <url> '<expr>' --start=<t>`
Query over time

`promtool check metrics`
Lint metrics from stdin

`promtool tsdb analyze <dir>`
Find cardinality hogs

`promtool help <command>`
Help for a command

Write rules rules.yml → `check rules` → **Unit test** tests.yml → `test rules` → **Check config** prometheus.yml → `reload` → **Live server** query to verify

Typical rule workflow

CONCEPTS

promtool ships in the Prometheus release tarball and works offline on files; only query, push and debug talk to a server.

Exit code 0 means ok, 1 an error, and 3 a lint finding when --lint-fatal is set, so every check fits a CI step.

Commands marked experimental (promql, tsdb create-blocks-from, dump-openmetrics) need promtool --experimental.

CHECK

`promtool check config <file>`
Validate config and referenced rule files

`promtool check rules <rules.yml>`
Validate rule files

`promtool check config --syntax-only <file>`
Skip referenced files

`promtool check rules --lint=all <rules.yml>`
Enable all lint checks

`promtool check config --lint-fatal <file>`
Exit 3 on lint findings

`promtool check config --lint=none <file>`
Disable linting

`promtool check config --agent <file>`
Validate for Agent mode

`promtool check rules --ignore-unknown-fields <rules.yml>`
Tolerate unknown YAML keys

`promtool check web-config <file>`
Validate the web config (TLS/auth)

`promtool check service-discovery <file> <job>`
Show targets after relabeling

`promtool check metrics < <file>`
Lint metric names and types from stdin

CHECK (cont.)

`promtool check metrics --extended < <file>`
Add cardinality info

`promtool check healthy --url=<url>`
Is the server healthy?

`promtool check ready --url=<url>`
Is the server ready?

`promtool check healthy --http.config.file=<f> --url=<url>`
Check with auth/TLS settings

TEST RULES

`promtool test rules <tests.yml>`
Run rule unit tests

`promtool test rules <a.yml> <b.yml>`
Run several test files

`promtool test rules --run=<group> <tests.yml>`
Run only matching test groups

`promtool test rules --debug <tests.yml>`
Print evaluation detail

`promtool test rules --junit=<out.xml> <tests.yml>`
Write JUnit XML for CI

`promtool test rules --diff <tests.yml>`
Show diff on failure

(experimental)

Test file keys

Key	Purpose
`rule_files`	Rule files under test
`evaluation_interval`	Rule eval step (default 1m)
`tests[].interval`	Sample step for input_series
`input_series`	series + values pairs
`alert_rule_test`	eval_time, alertname, exp_alerts
`promql_expr_test`	expr, eval_time, exp_samples

Series value notation

Value	Means
`1+2x3`	1 3 5 7 (start, step, count)
`5x3`	5 5 5 5
`_`	missing sample
`stale`	stale marker
`_x3`	three gaps

TEST RULES (cont.)

In a test file, rule_files paths are relative to the test file, not to your shell directory.

QUERY A SERVER

`promtool query instant <url> '<expr>'`
Run an instant query

`promtool query range <url> '<expr>' --start=<t> --end=<t> --step=1m`
Run a range query

`promtool query instant --time=<t> <url> '<expr>'`
Evaluate at a point in time

`promtool query series <url> --match='<selector>'`
List matching series

`promtool query labels <url> <label>`
List values of a label

`promtool query labels <url> __name__`
List all metric names

`promtool query instant -o json <url> '<expr>'`
Output JSON instead of PromQL text

`promtool query instant --http.config.file=<f> <url> '<expr>'`
Use auth/TLS settings from a file

TSDB

`promtool tsdb list <dir>`
List blocks in a data dir

`promtool tsdb list -r <dir>`
Show human-readable times and sizes

`promtool tsdb analyze <dir>`
Cardinality and churn report

`promtool tsdb analyze --limit=50 <dir> <block-id>`
Top 50 for one block

`promtool tsdb dump <dir> --match='<selector>'`
Dump samples as text

`promtool tsdb dump --min-time=<ms> --max-time=<ms> <dir>`
Dump a time range (ms)

TSDB (cont.)

`promtool tsdb create-blocks-from openmetrics <file> <outdir>`
Backfill from OpenMetrics (experimental)

`promtool tsdb create-blocks-from rules --start=<t> --url=<url> <rules.yml>`
Backfill recording rules (experimental)

PUSH, DEBUG, PROMQL

`promtool push metrics <write-url> <file>`
Send samples via remote write

`promtool debug all <url>`
Collect profiles and metrics archive

`promtool --experimental promql format '<expr>'`
Pretty-print a query

`promtool --version`
Print the version

`promtool --help`
List all commands

RECIPES

Validate before deploy

```
promtool check config prometheus.yml
promtool check rules rules/*.yml
promtool test rules tests/*.yml
```

Reload after a successful check

```
promtool check config prometheus.yml \
  && curl -X POST localhost:9090/-/reload
```

Minimal alert unit test (tests.yml)

```
rule_files: [rules.yml]
tests:
  - interval: 1m
    input_series:
      - series: 'up{job="api"}'
        values: '1 1 0 0 0 0'
    alert_rule_test:
      - eval_time: 5m
        alertname: ApiDown
        exp_alerts:
          - exp_labels: {job: api}
```

Find the biggest series sets

```
promtool tsdb analyze data/ | head -40
promtool query labels http://localhost:9090 __name__
```