Proxmox VE Virtualization platform CLI

START HERE

`qm` **`list`**
VMs on this node

`pct enter` *`<vmid>`*
Root shell in a container

`pct list`
Containers on this node

`qm` **`config`** *`<vmid>`*
Show a VM's settings

`qm` **`start`** *`<vmid>`*
Boot a VM

`vzdump` *`<vmid>`* **`--storage`** *`<storage>`*
Back up a guest

`qm` **`shutdown`** *`<vmid>`*
Clean ACPI power-off

`pvesm status`
Storages and free space

CONCEPTS

qm manages QEMU/KVM VMs, pct manages LXC containers. Both share one ID space: every guest has a unique numeric VMID (100 and up) across the cluster.

Cluster pvecm, /etc/pve shared
Node one PVE host
Guest VM (qm) or CT (pct), by VMID
Volume <storage>:<volume> on a storage

Disks, ISOs, templates and backups are addressed by volume ID, storage:name, e.g. local-lvm:vm-100-disk-0 or local:iso/<file>.iso.

Guest configs are plain files: /etc/pve/qemu-server/<vmid>.conf and /etc/pve/lxc/<vmid>.conf. Prefer qm set / pct set over editing them.

VM LIFECYCLE

`qm` **`list`**
List VMs with status, memory, PID

`qm` **`start`** *`<vmid>`*
Start a VM

`qm` **`shutdown`** *`<vmid>`*
Ask the guest to shut down
Sends ACPI; --timeout <s> --forceStop 1 kills it if it hangs.

`qm` **`stop`** *`<vmid>`*
Hard stop, like pulling the plug

`qm` **`reboot`** *`<vmid>`*
Clean reboot

`qm` **`status`** *`<vmid>`*
Running or stopped

`qm` **`unlock`** *`<vmid>`*
Clear a stale lock
For a lock left by a crashed backup, snapshot or migration.

`qm` **`destroy`** *`<vmid>`* **`--purge`**
Delete the VM and its disks
--purge also drops it from backup jobs, HA and replication.

VM CONSOLE & GUEST AGENT

`qm` **`terminal`** *`<vmid>`*
Attach to the serial console
Needs a serial port (qm set <vmid> --serial0 socket). Exit with Ctrl+O.

VM CONSOLE & GUEST AGENT (cont.)

`qm` **`set`** *`<vmid>`* **`--agent enabled=1`**
Enable the QEMU guest agent
The guest must run qemu-guest-agent too.

`qm` **`guest cmd`** *`<vmid>`* **`network-get-interfaces`**
Guest IP addresses via the agent

VM CONFIGURATION

`qm` **`config`** *`<vmid>`*
Show the VM's settings
--current shows the running values instead of pending ones.

`qm` **`set`** *`<vmid>`* **`--memory`** *`<MiB>`*
Set RAM

`qm` **`set`** *`<vmid>`* **`--cores`** *`<n>`*
Set CPU cores

`qm` **`set`** *`<vmid>`* **`--onboot 1`**
Start with the node

`qm` **`set`** *`<vmid>`* **`--net0 virtio,bridge=vmbr0`**
Add or change a NIC

`qm` **`pending`** *`<vmid>`*
Changes waiting for a restart

`qm` **`create`** *`<vmid>`* **`--name`** *`<name>`* **`--memory 2048`**
Create an empty VM
Add --net0 virtio,bridge=vmbr0 and a disk such as --scsi0 <storage>:32.

`qm` **`disk resize`** *`<vmid>`* **`scsi0 +10G`**
Grow a disk
Without + the size is absolute. Grow the partition inside the guest afterwards.

`qm` **`disk import`** *`<vmid>`* *`<image>`* *`<storage>`*
Import an image as a new disk
Lands as unusedN; attach it with qm set --scsi0 or use --target-disk.

TEMPLATES, CLONES & SNAPSHOTS

`qm` **`snapshot`** *`<vmid>`* *`<name>`*
Take a snapshot
Add --vmstate 1 to include RAM of a running VM.

`qm` **`listsnapshot`** *`<vmid>`*
List snapshots

`qm` **`rollback`** *`<vmid>`* *`<name>`*
Revert to a snapshot

`qm` **`delsnapshot`** *`<vmid>`* *`<name>`*
Delete a snapshot

TEMPLATES, CLONES & SNAPSHOTS (cont.)

`qm` **`template`** *`<vmid>`*
Turn a VM into a template
One way only; templates cannot be started.

`qm` **`clone`** *`<vmid>`* *`<newid>`* **`--name`** *`<name>`*
Clone a VM or template
From a template the default is a linked clone; --full 1 copies the disks.

CONTAINERS (PCT)

`pct list`
List containers

`pct create` *`<vmid>`* *`<template>`* **`--rootfs`** *`<storage>:<GiB>`*
Create a container
<template> is a volume ID like local:vztmpl/<file>. Add --hostname, --net0 and --unprivileged 1.

`pct start` *`<vmid>`*
Start a container

`pct enter` *`<vmid>`*
Root shell inside

`pct shutdown` *`<vmid>`*
Clean shutdown

`pct stop` *`<vmid>`*
Kill the container

`pct exec` *`<vmid>`* **`--`** *`<cmd>`*
Run one command inside

`pct config` *`<vmid>`*
Show the container's settings

`pct set` *`<vmid>`* **`--memory`** *`<MiB>`* **`--cores`** *`<n>`*
Change resources

`pct push` *`<vmid>`* *`<file>`* *`<dest>`*
Copy a file into it

CONTAINER TEMPLATES (PVEAM)

`pveam update`
Refresh the template index

`pveam available --section system`
List downloadable OS templates

`pveam download` *`<storage>`* *`<template>`*
Download a template

STORAGE (PVESM)

`pvesm status`
Storages with type and usage

`pvesm list` *`<storage>`*
Volumes on a storage

BACKUP & RESTORE

`vzdump` *`<vmid>`* **`--storage`** *`<storage>`*
Back up a VM or container
Default mode is snapshot: live, no downtime.

`vzdump` *`<vmid>`* **`--mode stop --compress zstd`**
Consistent backup, stops the guest

`pvesm list` *`<storage>`* **`--content backup`**
List backup archives

`qmrestore` *`<archive>`* *`<vmid>`* **`--storage`** *`<storage>`*
Restore a VM backup
Restoring onto an existing VMID needs --force 1. --unique 1 makes new MACs.

`pct restore` *`<vmid>`* *`<archive>`* **`--storage`** *`<storage>`*
Restore a container backup

MIGRATION

`qm` **`migrate`** *`<vmid>`* *`<node>`*
Move a stopped VM to another node

`qm` **`migrate`** *`<vmid>`* *`<node>`* **`--online`**
Live-migrate a running VM

CLUSTER & API

`pvecm status`
Quorum and membership

`pvecm nodes`
Cluster nodes and votes

`pvesh get /cluster/resources --type vm`
Every guest in the cluster

`pveversion`
Proxmox VE version

RECIPES

Cloud-init VM template

```
qm create 9000 --name tpl --
memory 2048 --net0
virtio,bridge=vmbr0 --scsihw
virtio-scsi-pci
qm set 9000 --scsi0 local-
lvm:0,import-from=/root/
<cloudimg>.img
qm set 9000 --ide2 local-
lvm:cloudinit --boot order=scsi0
qm set 9000 --serial0 socket --
vga serial0
qm template 9000
```

New VM from the template

```
qm clone 9000 123 --name web1 --
full 1
qm set 123 --sshkey ~/.ssh/
id_rsa.pub
qm set 123 --ipconfig0
ip=10.0.10.123/24,gw=10.0.10.1
qm start 123
```