Pulumi Infrastructure as code

CONCEPTS

Your program declares the desired resources in a real language. Pulumi diffs that against the stack's stored state and applies only the difference.

Program code per project
↓ preview
Engine diff vs state
↓ up
Stack one environment
↓ provider API
Cloud resources real infrastructure

A project is the code (Pulumi.yaml); a stack is one deployed instance of it (dev, prod) with its own config and state (Pulumi.<stack>.yaml).

Preview before up on shared stacks, and use pulumi refresh if someone changed resources by hand.

PROJECTS & DEPLOYS

pulumi new *<template>*
Create a project from a template

pulumi preview
Show what up would change

pulumi preview --diff
Preview as a rich diff

pulumi up
Preview, confirm, then deploy

pulumi up --yes
Deploy without the prompt

pulumi destroy
Delete all resources in the stack

pulumi refresh
Update state from the real cloud

TARGETING

pulumi up --replace *<urn>*
Force recreating a resource

TARGETING (cont.)

pulumi stack --show-urns
List resources with their URNs

STACKS

pulumi stack init *<name>*
Create a stack

pulumi stack ls
List stacks

pulumi stack select *<name>*
Switch the current stack

pulumi stack
Show current stack and resources

pulumi stack output
Show all outputs

pulumi stack output *<name>*
Print one output value

pulumi stack output --json
Outputs as JSON

CONFIG & SECRETS

pulumi config
List config values

pulumi config set *<key> <value>*
Set a config value

pulumi config set --secret *<key> <value>*
Store a value encrypted

pulumi config get *<key>*
Read one value

BACKENDS & STATE

pulumi login
Log in to Pulumi Cloud

pulumi login s3://*<bucket>*
Use an S3 bucket as backend

IMPORT & LOGS

pulumi import *<type> <name> <id>*
Adopt an existing resource