pytest Python test runner

START HERE

pytest
Run all tests

pytest -s
Show print output

pytest <path>::<test>
Run one test

pytest --pdb
Debug on failure

pytest -k "<expr>"
Filter by name

pytest -x
Stop at first failure

pytest --lf
Rerun last failures

pytest -v
One line per test

Collect find tests → **filter -k -m** → **Setup** fixtures → **run** → **Call** test body → **teardown** → **Report** pass / fail

CONCEPTS

Files named test_*.py or *_test.py, functions named test_*, are collected; plain assert is all you need.

Fixtures in conftest.py are shared with every test below that directory, with no import.

SELECT TESTS

pytest <dir> / <file.py>
Run a directory or file

pytest <file.py>::<test>
Run one test function

pytest <file.py>::<Class>::<method>
Run one method of a class

pytest "<file.py>::<test>[<id>]"
Run one parametrized case

pytest -k "a and not b"
Select by name expression
Case-insensitive substring match on test, class and module names.

pytest -m <marker>
Select by marker

pytest -m "not slow"
Skip a marker

pytest --collect-only -q
List test ids without running

pytest --deselect <nodeid>
Drop one test by id

RUN CONTROL

pytest -x
Stop at first failure

pytest --maxfail=<n>
Stop after n failures

pytest --lf
Rerun only last failures

pytest --ff
Failures first, then the rest

pytest --sw
Stop, resume at that test next run

pytest --durations=<n>
Show n slowest tests

OUTPUT

pytest -v / -vv
More detail per test

pytest -q
Quieter output

pytest -s
Do not capture stdout

pytest --tb=short
Compact tracebacks
Styles: auto, long, short, line, native, no.

pytest -l
Show locals in tracebacks

pytest -ra
Summary of all but passed
Letters: f E s x X p P a A; default is fE.

pytest --junitxml=<file>
Write a JUnit XML report

OUTPUT (cont.)

pytest --log-cli-level=INFO
Live log output

DEBUGGING

pytest --pdb
Open pdb at a failure

pytest --trace
Break at the start of each test

breakpoint()
Drop into the debugger here
Capturing is paused while the prompt is active.

pytest --setup-show
Show fixture setup and teardown

pytest --fixtures
List available fixtures

pytest --markers
List registered markers

FIXTURES

@pytest.fixture
Declare a fixture

def test_x(<fixture>):
Request a fixture by argument name

yield <value>
Setup before, teardown after

@pytest.fixture(scope="<s>")
Share across tests
Scopes: function (default), class, module, package, session.

FIXTURES (cont.)

@pytest.fixture(autouse=True)
Apply to every test in scope

@pytest.fixture(params=<list>)
Run tests once per value

request.param
Current value of a param fixture

@pytest.mark.usefixtures
Use fixtures without arguments

conftest.py
Directory-wide shared fixtures

Fixture with teardown

```
@pytest.fixture
def db():
    conn = connect()
    yield conn
    conn.close()
```

PARAMETRIZE AND MARKS

@pytest.mark.parametrize("a,b", [(1, 2), (3, 4)])
Run a test per data row

pytest.param(<v>, id="<name>")
Name one case

@pytest.mark.skip
Always skip (reason="<why>")

@pytest.mark.skipif(<cond>)
Skip on a condition (add reason=)

PARAMETRIZE AND MARKS (cont.)

@pytest.mark.xfail
Expected to fail (reason="<why>")

pytest.skip("<why>")
Skip from inside a test

pytestmark = pytest.mark.<name>
Mark a whole module

Stacked parametrize decorators produce every combination of their values.

ASSERTIONS AND BUILT-INS

assert <expr>
Plain assert with rich diffs

with pytest.raises(<Exc>):
Expect an exception

pytest.raises(<Exc>, match="<re>")
Check the message by regex

pytest.approx(<x>)
Compare floats with tolerance

tmp_path
Temporary directory per test

monkeypatch
Patch attrs, env, dicts

capsys
Capture stdout and stderr

caplog
Inspect log records

ASSERTIONS AND BUILT-INS (cont.)

monkeypatch.setenv("<K>", "<v>")
Set an env var for one test

monkeypatch.setattr(<obj>, "<name>", <val>)
Replace an attribute

CONFIG

[tool.pytest]
pyproject table (pytest 9+)
Older versions use [tool.pytest.ini_options]. pytest.toml and pytest.ini also work.

testpaths = ["tests"]
Where to look by default

addopts = ["-ra", "-q"]
Options added to every run

markers = ["slow: slow tests"]
Register custom markers

--strict-markers
Error on unregistered markers

RECIPES

Table-driven test

```
@pytest.mark.parametrize("s,n",
[
    ("1", 1),
    (" 2 ", 2),
    pytest.param("x", 0,
id="bad"),
])
def test_parse(s, n):
    assert parse(s) == n
```