Python CLI

Interpreter and -m tools

CONCEPTS

python3 -m <module> runs a module from the import path, so tools like venv, pip and pytest always match the interpreter you called.

RUN CODE

`python3 <script.py> <args>`
Run a script

`python3 -c "<code>"`
Run code from a string

`python3 -m <module> <args>`
Run a module as a script

`python3 -V`
Print the version

INTERACTIVE

`python3`
Start the REPL

`python3 -i <script.py>`
Run script, then stay in the REPL

`_`
Last result in the REPL

`help(<obj>)`
Show docs for an object

`dir(<obj>)`
List attributes of an object

VIRTUAL ENVS AND PACKAGES

`python3 -m venv .venv`
Create a virtual environment

`source .venv/bin/activate`
Activate it (Linux, macOS)

`deactivate`
Leave the environment

`.venv/bin/python <script.py>`
Use a venv without activating

`python3 -m pip install <pkg>`
Install a package

`python3 -m pip install -r requirements.txt`
Install from a list

`python3 -m pip install -e .`
Editable install of this project

DEV SERVERS AND TOOLS

`python3 -m http.server`
Serve current dir on port 8000

`python3 -m http.server <port>`
Serve on another port

`python3 -m http.server -b 127.0.0.1`
Listen on localhost only

`python3 -m json.tool <file>`
Validate and pretty-print JSON

TEST AND DEBUG

`python3 -m pdb <script.py>`
Debug a script from the first line

`python3 -m pdb -c continue <script.py>`
Debug, stopping on a crash

`breakpoint()`
Drop into the debugger from code

`n / s / c / q`
pdb: next, step, continue, quit

`python3 -m unittest`
Discover and run unittest tests

`python3 -X dev <script.py>`
Development mode: extra checks

MEASURE

`python3 -m timeit "<stmt>"`
Time a small statement

`python3 -m timeit -s "<setup>" "<stmt>"`
Time with a setup step

`python3 -m cProfile -s cumtime <script.py>`
Profile, sorted by cumulative time

FLAGS AND BEHAVIOUR

`python3 -u <script.py>`
Unbuffered stdout and stderr

ENVIRONMENT VARIABLES

`PYTHONPATH=<dir>[:<dir>]`
Extra module search directories

`PYTHONUNBUFFERED=1`
Same as -u, good for logs and containers