qutebrowser Keyboard-driven browser

CONCEPTS

Modal like vim: normal mode browses, i enters insert mode for typing in fields, Esc returns. Keys on this sheet are normal mode.

Normal browse
Insert
↓ i
Normal
↓ Esc
Command
↓ :

A number before a key repeats it or targets a tab, e.g. 5J moves five tabs right. Most keys are just commands: use :bind to see or change them.

Prefix a command with :help for docs, e.g. :help :open or :help tabs.show.

NAVIGATION

h / j / k / l
Scroll left / down / up / right

gg / G Top / bottom of page

Ctrl + d / Ctrl + u
Half page down / up

Ctrl + f / Ctrl + b
Page down / up

H / L
Back / forward in history

r / R
Reload / reload bypassing cache

o Open URL in current tab

O Open URL in new tab

go Edit current URL

gO Edit current URL in new tab

gu Go up one URL level

Plus / Minus Zoom in / out

HINTS

f Follow link in current tab

F Follow link in new tab

;y Hint link, yank its URL

HINTS (cont.)

;b
Hint link, open in background tab

Hints are typed live: once only one label still matches, it fires. Type some of the link text instead of the label to filter.

TABS

J Next tab

K Previous tab

d Close tab

u Undo closed tab

Alt + 1-9 Go to tab by position

gt Pick tab by number or name

g0 / g$ First / last tab

co Close all other tabs

gJ / gK Move tab right / left

Ctrl + Tab Last used tab

T Select tab from a list

SEARCH & CLIPBOARD

/ Search forward

? Search backward

n / N Next / previous match

yy Yank page URL

yt Yank page title

pp Open clipboard URL

Pp
Open clipboard URL in new tab

BOOKMARKS

m
Save quickmark for this page

b Load quickmark

B Load quickmark in new tab

M Bookmark this page

COMMAND MODE

: Open command line

COMMAND MODE (cont.)

:open *<url>*
Open URL (or search term)

:open -t *<url>*
Open in new tab

:q
Quit qutebrowser

:wq
Save session and quit

:set *<option> <value>*
Change a setting for this run

:config-edit
Edit config.py

:config-source
Reload config.py

:help *<topic>*
Open built-in docs

:bind *<key> <cmd>*
Bind a key

:adblock-update
Update ad block lists

Ctrl + p / Ctrl + n
Previous / next command in history (command line)

Tab / Shift + Tab
Complete command (command line)

INSERT & PASSTHROUGH

i Enter insert mode

Esc Back to normal mode

Ctrl + e
Edit field in external editor (insert mode)

gi Focus first input field

RECIPES

Starter config.py

```
# ~/.config/qutebrowser/config.py
config.load_autoconfig()
c.url.searchengines = {'DEFAULT':
'https://duckduckgo.com/?q={}'}
c.tabs.show = 'multiple'
c.content.blocking.enabled = True
config.bind('<Ctrl+Shift+t>',
'undo')
```

Reload after editing

```
:config-edit
# edit, save, then
:config-source
```