qutebrowser Keyboard-driven browser

Normal browse | **Insert** | `i` → **Normal** | `Esc` → **Command** | `:` →

CONCEPTS

Modal like vim: normal mode browses, i enters insert mode for typing in fields, Esc returns. Keys on this sheet are normal mode.

A number before a key repeats it or targets a tab, e.g. 5J moves five tabs right. Most keys are just commands: use :bind to see or change them.

NAVIGATION

`h` / `j` / `k` / `l`
Scroll left / down / up / right

`gg` / `G`
Top / bottom of page

`Ctrl`+`d` / `Ctrl`+`u`
Half page down / up

`Ctrl`+`f` / `Ctrl`+`b`
Page down / up

`H` / `L`
Back / forward in history

`r` / `R`
Reload / reload bypassing cache

`o` Open URL in current tab

`O` Open URL in new tab

NAVIGATION (cont.)

`go` Edit current URL

`Plus` / `Minus`
Zoom in / out

HINTS

`f` Follow link in current tab

`F` Follow link in new tab

`;y` Hint link, yank its URL

`;b`
Hint link, open in background tab

Hints are typed live: once only one label still matches, it fires. Type some of the link text instead of the label to filter.

TABS

`J` Next tab

`K` Previous tab

`d` Close tab

`u` Undo closed tab

`Alt`+`1-9`
Go to tab by position

`gt`
Pick tab by number or name

TABS (cont.)

`g0` / `g$` First / last tab

`co` Close all other tabs

`gJ` / `gK`
Move tab right / left

`Ctrl`+`Tab` Last used tab

`T` Select tab from a list

SEARCH & CLIPBOARD

`/` Search forward

`?` Search backward

`n` / `N`
Next / previous match

`yy` Yank page URL

`yt` Yank page title

`pp` Open clipboard URL

`Pp`
Open clipboard URL in new tab

BOOKMARKS

`m`
Save quickmark for this page

`b` Load quickmark

BOOKMARKS (cont.)

`B`
Load quickmark in new tab

`M` Bookmark this page

COMMAND MODE

`:` Open command line

`:open` *`<url>`*
Open URL (or search term)

`:open -t` *`<url>`*
Open in new tab

`:q`
Quit qutebrowser

`:wq`
Save session and quit

`:set` *`<option>`* *`<value>`*
Change a setting for this run

`:config-edit`
Edit config.py

`:config-source`
Reload config.py

`:help` *`<topic>`*
Open built-in docs

`:bind` *`<key>`* *`<cmd>`*
Bind a key

`:adblock-update`
Update ad block lists

`Ctrl`+`p` / `Ctrl`+`n`
Previous / next command in history (command line)

COMMAND MODE (cont.)

`Tab` / `Shift`+`Tab`
Complete command (command line)

INSERT & PASSTHROUGH

`i` Enter insert mode

`Esc` Back to normal mode

`Ctrl`+`e`
Edit field in external editor (insert mode)

`gi` Focus first input field

RECIPES

Starter config.py

```
# ~/.config/qutebrowser/
config.py
config.load_autoconfig()
c.url.searchengines =
{'DEFAULT': 'https://
duckduckgo.com/?q={}'}
c.tabs.show = 'multiple'
c.content.blocking.enabled =
True
config.bind(
'<Ctrl+Shift+t>', 'undo')
```

Reload after editing

```
:config-edit
# edit, save, then
:config-source
```