Racket Language and raco tools

CONCEPTS

A file starts with #lang racket (or racket/base, typed/racket, ...). Running racket <file> requires that module and runs its main submodule if present.

Write #lang racket in app.rkt
↓ `raco make`
Compile compiled/*.zo bytecode
↓ `raco test`
Test test submodule
↓ `raco exe`
Ship executable + distribute

racket with a file argument does not open a REPL. Add -i to run the file and then stay in the REPL.

raco is the tool launcher: raco help lists every command installed, and packages can add their own (raco fmt).

RUN RACKET

`racket`
Start the REPL

`racket` *<file.rkt>* **`[`***<args>***`...]`**
Run a module with arguments

`racket -e '`*<expr>***`'`**
Evaluate an expression and print it

`racket -l racket/base -e '`*<expr>***`'`**
Eval with a fast-loading language

`racket -i` *<file.rkt>*
Run a file, then enter the REPL

`racket -t` *<file.rkt>*
Require a file and its main submodule

`racket -l` *<lib>*
Require a library collection path

`racket -v`
Print the version banner

THE REPL

`(exit) / Ctrl+D`
Leave the REPL

`,help`
Show REPL help

THE REPL (cont.)

`,enter` *<file.rkt>*
Enter a module's namespace

`,require` *<module>*
Require a module

`,reload`
Reload the last required module

Lines starting with a comma are REPL commands, not Racket code. Use ,enter to test a file's private definitions.

RACO MAKE AND EXE

`raco make` *<file.rkt>*
Compile a module and its dependencies

`raco exe -o` *<out>* *<file.rkt>*
Build a stand-alone executable

`raco distribute` *<dir>* *<exe>*
Package an exe with its runtime files

Executables are tied to the OS and architecture that built them. Run raco distribute before copying one to another machine.

TESTS

`raco test` *<file.rkt>*
Run a module's test submodules

`raco test` *<dir>*
Test all modules in a directory

`(module+ test ...)`
Add tests inside the module

`(require rackunit)`
Load the unit-test library

`(check-equal?` *<actual>* *<expected>***`)`**
Check two values are equal

PACKAGES

`raco pkg install` *<pkg>*
Install a package from the catalog

`raco pkg install --auto` *<pkg>*
Install and fetch missing dependencies

`raco pkg update` *<pkg>*
Update a package

PACKAGES (cont.)

`raco pkg remove` *<pkg>*
Uninstall a package

`raco pkg show`
List installed packages

`raco pkg install --link` *<dir>*
Link a local directory as a package

TOOLS AND DOCS

`raco docs` *<term>*
Search the documentation

`raco fmt` *<file.rkt>*
Print the formatted program

`raco fmt -i` *<file.rkt>*
Format in place

LANGUAGE BASICS

`#lang racket`
Full language with common libraries

`#lang racket/base`
Small, fast-loading language

`(require` *<module>***`)`**
Import a library or file

`(require "`*<file.rkt>***`")`**
Import a sibling file by path

`(provide` *<id>* **`...)`**
Export bindings from a module

`(define (`*<f>* *<x>***`) ...)`**
Define a function

`(module+ main ...)`
Code run by racket <file>

`(define args (current-command-line-arguments))`
Read command-line arguments

RECIPES

Script with tests

```
#lang racket/base
(provide add)
(define (add a b) (+ a b))
(module+ test
  (require rackunit)
  (check-equal? (add 1 2) 3))
(module+ main
  (displayln (add 1 2)))
```

Compile, test, ship

```
raco make main.rkt
raco test .
raco exe -o app main.rkt
raco distribute dist app
```