rebar3 Erlang build tool

START HERE

`rebar3 new app <name>`
Create an OTP app

`rebar3 as prod tar`
Release tarball

`rebar3 compile`
Fetch deps and build

`rebar3 help <task>`
Help for a task

`rebar3 shell`
Erlang shell with the project

`rebar3 eunit`
Run unit tests

`rebar3 ct`
Run Common Test suites

`rebar3 dialyzer`
Type analysis

rebar.config deps, profiles → `compile` → **rebar.lock** pinned deps → `build` → **_build/<profile>** beams, deps, rel → `release / tar` → **Release** relx, start script

CONCEPTS

rebar3 is the Erlang build tool: one rebar.config per project, builds land in _build/<profile>. Run rebar3 help to list tasks, including plugin ones.

Profiles pick the build variant: default, test (used by eunit and ct) and prod. Select with rebar3 as <profile> <task>.

PROJECTS

`rebar3 new app <name>`
OTP application with supervisor

`rebar3 new lib <name>`
Library without a supervisor

`rebar3 new release <name>`
Umbrella project for releases
umbrella is an alias of the release template; apps go under apps/.

`rebar3 new escript <name>`
Command-line escript project

`rebar3 new help`
List available templates

BUILD & RUN

`rebar3 compile`
Fetch deps and compile all apps

`rebar3 clean`
Remove compiled beams

BUILD & RUN (cont.)

`rebar3 clean --all`
Clean deps and all profiles too

`rebar3 shell`
Shell with apps and deps loaded
Starts the apps in the shell; use --start-clean to load code without starting them.

`rebar3 shell --sname <name>`
Shell as a named node

`rebar3 shell --apps <a>,<b>`
Start only these apps

`rebar3 shell --config <file>`
Use a sys.config file

`rebar3 do <task>,<task>`
Run several tasks in a row

`rebar3 escriptize`
Package an escript executable

`rebar3 version`
Show rebar3 and Erlang versions

TEST

`rebar3 eunit`
Run all EUnit tests

`rebar3 eunit --module=<mod>`
Tests of one module

`rebar3 eunit --test=<mod>:<fun>`
Run one test function

TEST (cont.)

`rebar3 eunit --application=<app>`
Tests of one app

`rebar3 eunit -v`
Verbose output

`rebar3 ct`
Run all Common Test suites
*Suites are *_SUITE.erl files in each app's test/ directory.*

`rebar3 ct --suite=<path>`
Run one suite
Comma-separate several suites; the path has no .erl extension.

`rebar3 ct --suite=<path> --group=<g>`
Run one test group

`rebar3 ct --suite=<path> --case=<c>`
Run one test case

`rebar3 ct --sys_config=<file>`
Use a sys.config for tests

`rebar3 eunit --cover`
Collect coverage data

`rebar3 ct --cover`
Collect coverage data

`rebar3 cover --verbose`
Coverage report in the console

`rebar3 do eunit,ct`
Run both test types

DEPENDENCIES

`rebar3 deps`
List deps and lock status

DEPENDENCIES (cont.)

`rebar3 tree`
Show the dependency tree

`rebar3 upgrade`
Upgrade all dependencies

`rebar3 upgrade <dep>`
Upgrade one dependency
Also upgrades the subtree of that dependency.

`rebar3 update`
Refresh the Hex package index

deps in rebar.config

```
{deps, [
  cowboy,
  {jsx, "~> 3.1"},
  {mylib, {git, "<url>", {tag,
"1.0.0"}}},
  {other, {git, "<url>",
{branch, "main"}}}
]}.
```

Work on a dependency locally by putting a copy or symlink in _checkouts/. The deps entry must still exist.

List every dependency in the .app.src applications list too, or it will not start with your app.

PROFILES

`rebar3 as <profile> <task>`
Run a task in a profile

`rebar3 as <p1>,<p2> <task>`
Combine profiles

`rebar3 as test compile`
Build with test profile deps

PROFILES (cont.)

profiles in rebar.config

```
{profiles, [
  {test, [{deps, [meck]}]},
  {prod, [{erl_opts,
[no_debug_info]}]}
]}.
```

QUALITY

`rebar3 dialyzer`
Build the PLT and check types
The first run builds a PLT and is slow; later runs reuse it.

`rebar3 xref`
Cross-reference check

`rebar3 edoc`
Generate API docs

Checks in rebar.config

```
{dialyzer, [{warnings,
[no_return]}]}.
{xref_checks,
[undefined_function_calls,
 exports_not_used]}.
{cover_enabled, true}.
```

RELEASES

`rebar3 release`
Build a dev release

`rebar3 as prod release`
Release with ERTS, no symlinks

`rebar3 as prod tar`
Release as a .tar.gz

`_build/<profile>/rel/<name>/bin/<name> console`
Start a release in a shell

RELEASES (cont.)

`bin/<name> foreground`
Run in foreground (systemd, Docker)

`bin/<name> daemon`
Run as a background node

`bin/<name> remote_console`
Attach to a running node

`bin/<name> ping / stop / restart`
Control a running node

relx in rebar.config

```
{relx, [
  {release, {<name>, "0.1.0"},
[<name>, sasl]},
  {dev_mode, true},
  {include_erts, false},
  {extended_start_script, true}
]}.
```

CONFIG & PLUGINS

Compile options

```
{erl_opts, [debug_info,
 warnings_as_errors]}.
{minimum_otp_vsn, "26"}.
```

Aliases and hooks

```
{alias, [{check, [xref,
dialyzer, eunit, ct]}]}.
{provider_hooks, [{pre,
[{compile, clean}]}]}.
```

Plugins

```
{plugins, [rebar3_auto]}.
{project_plugins, [erlfmt]}.
```

HEX

`rebar3 hex publish`
Publish package and docs