RuboCop Ruby linter and formatter

Run rubocop reads .rubocop.yml → offenses → **Autocorrect** -a safe, -A unsafe → leftovers → **Fix by hand** or disable a cop → commit → **Clean exit 0** CI gate

CONCEPTS

A cop is one rule; cops belong to departments such as Style, Layout, Lint, Metrics, Naming, Security.

Safe autocorrect (-a) keeps behaviour; unsafe (-A) may change it. Review the diff after -A.

Exit codes: 0 clean, 1 offenses found, 2 crash or bad config or options.

RUNNING

rubocop
Check all Ruby files here

`rubocop <path> ...`
Check given files or dirs

`rubocop -L`
List files that would be inspected

`rubocop -F`
Stop after first file with offenses

`rubocop --parallel`
Use all CPUs

`rubocop -s <path> < <file>`
Check stdin as if at path

RUNNING (cont.)

`rubocop --force-exclusion <path>`
Honour Exclude for explicit paths

`rubocop -c <file>`
Use another config file

`rubocop -v / -V`
Show version / full versions

CHOOSING COPS

`rubocop --only <Cop>,<Dept>`
Run only these cops or departments

`rubocop --except <Cop>`
Run all but these

`rubocop -l`
Lint cops only

`rubocop --safe`
Skip cops not marked safe

`rubocop --show-cops [<Cop>]`
Print cops and their settings

AUTOCORRECT

`rubocop -a`
Fix safe offenses

`rubocop -A`
Fix safe and unsafe offenses

`rubocop -x`
Fix layout offenses only

AUTOCORRECT (cont.)

`rubocop -a --only <Cop>`
Fix one cop everywhere

`rubocop -A --only Style/<Cop>`
Roll out a style change

OUTPUT

`rubocop -f <name>`
Pick an output formatter

`rubocop -f simple`
Offenses grouped by file

`rubocop -f offenses`
Count offenses per cop

`rubocop -f worst`
Files with most offenses

`rubocop -f files`
Only list offending files

`rubocop -f json -o <file>`
Machine readable report

`rubocop -E`
Show extra details in messages

CACHE AND SERVER

`rubocop -C false`
Disable the result cache

`rubocop --server`
Run via a background server

CACHE AND SERVER (cont.)

`rubocop --start-server / --stop-server`
Control the server

CONFIG FILES

`rubocop --init`
Write a starter .rubocop.yml

`rubocop --auto-gen-config`
Write .rubocop_todo.yml

`rubocop --regenerate-todo`
Redo the TODO file with last options

YAML KEYS

`inherit_from: <file>`
Include other configs

`plugins: - <name>`
Load extension plugins

`require: - <lib>`
Load extension by require

`AllCops: NewCops: enable`
Opt into pending cops

`AllCops: TargetRubyVersion: <x.y>`
Set Ruby version to parse as

`AllCops: Exclude: - <glob>`
Skip paths everywhere

YAML KEYS (cont.)

`<Dept>/<Cop>: Enabled: false`
Disable a cop

`<Dept>/<Cop>: Exclude: - <glob>`
Skip paths for one cop

`<Dept>/<Cop>: Max: <n>`
Tune a numeric limit

`<Dept>: Enabled: false`
Disable a whole department

INLINE COMMENTS

`# rubocop:disable <Cop>`
Turn off from here

`# rubocop:enable <Cop>`
Turn back on

`<code> # rubocop:disable <Cop>`
Disable for one line

`# rubocop:disable <Cop1>, <Cop2>`
Several cops at once

`# rubocop:disable <Dept>`
Whole department

RECIPES

Adopt on an old codebase

```
rubocop --auto-gen-config
rubocop -a
rubocop -f offenses
# then delete TODO entries
as you fix them
```