Scrapy Python web crawling

START HERE

`scrapy startproject <name>`
New project

`scrapy genspider <name> <domain>`
Spider skeleton

`scrapy shell "<url>"`
Try selectors live

`scrapy crawl <spider>`
Run a spider

`scrapy crawl <spider> -O out.json`
Save items

`scrapy list`
Spiders in project

`scrapy fetch "<url>"`
Download one page

`scrapy parse --spider=<name> "<url>"`
Debug a callback

Spider start requests → `Request` → **Downloader** fetches page → `Response` → **parse()** callback → `yield item` → **Item pipeline / feed** clean, store

CONCEPTS

Develop selectors in scrapy shell first, then paste them into the spider's parse().

Commands marked project-only (crawl, list, check, parse, edit) must run inside a folder with scrapy.cfg.

Quote URLs in the shell: an unquoted & ends the command.

PROJECT SETUP

`scrapy startproject <name> [dir]`
Create a project skeleton

`scrapy genspider <name> <domain>`
Create a spider from a template

`scrapy genspider -l`
List spider templates

`scrapy genspider -t crawl <name> <domain>`
Spider with link-following rules

`scrapy list`
List spiders in this project

RUNNING SPIDERS

`scrapy crawl <spider>`
Run a project spider

`scrapy runspider <file.py>`
Run a standalone spider file
Needs no project; settings come from the defaults or -s.

`scrapy crawl <spider> -a <name>=<value>`
Pass a spider argument
Arrives as a keyword argument of the spider's __init__.

`scrapy crawl <spider> -s <NAME>=<value>`
Override a setting once

`scrapy crawl <spider> -s DOWNLOAD_DELAY=1`
Slow down requests

RUNNING SPIDERS (cont.)

`scrapy crawl <spider> -L INFO`
Quieter log level

`scrapy crawl <spider> --nolog`
Disable logging

`scrapy crawl <spider> -s JOBDIR=<dir>`
Pause and resume a crawl
Stop with one Ctrl+C and rerun the same command to resume.

OUTPUT (FEEDS)

`scrapy crawl <spider> -o <file>`
Append items to a file
Format is guessed from the extension.

`scrapy crawl <spider> -O <file>`
Overwrite the file with items

`scrapy crawl <spider> -o <file>:<format>`
Force an output format

`scrapy crawl <spider> -O out.jsonl`
One JSON object per line

`scrapy crawl <spider> -O out.csv`
Write CSV

SHELL AND INSPECTION

`scrapy shell "<url>"`
Open the console on a page

`scrapy shell -c "response.css('title::text').get()" "<url>"`
One-shot expression

`scrapy fetch "<url>"`
Print the body as Scrapy sees it

`scrapy fetch --headers "<url>"`
Print response headers instead

`scrapy view "<url>"`
Open the page as Scrapy got it
Compare with your browser to spot JavaScript-rendered content.

SHELL AND INSPECTION (cont.)

`scrapy parse --spider=<name> "<url>"`
Run the spider's callback on one URL

`scrapy parse -c <callback> "<url>"`
Choose the callback

`scrapy settings --get <SETTING>`
Print one setting's value

SHELL OBJECTS AND SELECTORS

`response.css("<sel>")`
CSS selector on the page

`response.css("<sel>::text").getall()`
All matching text nodes

`response.css("<sel>::attr(href)").get()`
First attribute value or None

`response.xpath("//<tag>")`
XPath selector on the page

`view(response)`
Open the response in a browser

`fetch("<url>")`
Load another page into the shell

`inspect_response(response, self)`
Open a shell inside a running spider
Import from scrapy.shell; Ctrl+D resumes the crawl. fetch() does not work there.

SPIDER CODE

`yield {"<key>": <value>}`
Emit an item from parse()

`yield response.follow(<href>, callback=self.<fn>)`
Follow a link to another callback

`response.follow_all(css="<sel>", callback=self.<fn>)`
Follow every matching link

SPIDER CODE (cont.)

`yield scrapy.Request(<url>, callback=self.<fn>)`
Queue an explicit request

`cb_kwargs={"<key>": <value>}`
Pass data to the next callback

`custom_settings = {"<SETTING>": <value>}`
Per-spider settings

`start_urls = ["<url>"]`
Pages the spider begins on

`AUTOTHROTTLE_ENABLED = True`
Adapt speed to server load

RECIPES

New spider to JSON

```
scrapy startproject shop
cd shop
scrapy genspider books
books.toscrape.com
scrapy shell "https://books.
toscrape.com"
# edit spiders/books.py, then:
scrapy crawl books -O
books.json
```

Minimal standalone spider

```
# quotes.py
import scrapy
class Quotes(scrapy.Spider):
    name = "quotes"
    start_urls = ["https://
quotes.toscrape.com"]
    def parse(self, response):
        for q in
response.css("div.quote"):
            yield {"text":
q.css("span.text::text").get()}
        yield from response.
follow_all(css="li.next a",
callback=self.parse)

scrapy runspider quotes.py -O
quotes.jsonl
```

Polite, resumable crawl

```
scrapy crawl <spider> \
  -s JOBDIR=crawls/run1 \
  -s AUTOTHROTTLE_ENABLED=True
\
  -s DOWNLOAD_DELAY=1 \
  -O out.jsonl
```

Debug an empty result

```
scrapy fetch "<url>" >
page.html
scrapy view "<url>"
scrapy parse --spider=<name> -c
<callback> "<url>"
```