Serverless Framework Deploy Lambda from YAML

CONCEPTS

sls is a short alias for serverless. Every command reads serverless.yml in the current folder and defaults to stage dev.

serverless.yml functions + events
↓ package
.serverless/ zips + CloudFormation
↓ deploy
CloudFormation stack Lambda, API, IAM
↓ invoke / logs
Running service per stage and region

ACCOUNT

`serverless login`
Sign in and pick the default org

`serverless <command> --help`
Show help for one command

DEPLOY

`serverless deploy`
Deploy the whole service

`serverless deploy --stage <stage> --region <region>`
Deploy to another stage or region

`serverless deploy function -f <fn>`
Upload one function's code only

PACKAGE

`serverless package`
Build artifacts without deploying

INVOKE

`serverless invoke -f <fn>`
Call the deployed function

`serverless invoke -f <fn> --log`
Also print the invocation log

`serverless invoke -f <fn> -d '<json>'`
Pass an inline event

INVOKE (cont.)

`serverless invoke -f <fn> -p <file>`
Pass an event from a JSON file

LOCAL

`serverless invoke local -f <fn>`
Run a function on your machine

`serverless invoke local -f <fn> -p <file>`
Use an event file

`serverless invoke local -f <fn> -d '<json>'`
Use an inline event

`serverless dev`
Run deployed functions on local code

LOGS

`serverless logs -f <fn>`
Show the last 10 minutes of logs

`serverless logs -f <fn> -t`
Tail logs live

`serverless logs -f <fn> --startTime <time>`
Logs since 30m, 2h, 3d or a date

`serverless logs -f <fn> --filter <text>`
Only lines containing a pattern

INSPECT

`serverless info`
Show endpoints and functions

`serverless print`
Show config with variables resolved

ROLLBACK AND REMOVE

`serverless remove`
Delete the service from AWS

`serverless remove --stage <stage> --region <region>`
Delete one stage