shfmt Shell script formatter

CONCEPTS

Default output uses tabs. Pick your style once with flags or an .editorconfig, then let CI enforce it with -d.

Script *.sh or shebang
↓ parse
Syntax tree dialect rules
↓ print
Formatted code
flags / .editorconfig
↓ -w / -d / -l
Result file, diff or list

Any parser or printer flag on the command line makes shfmt ignore EditorConfig formatting options. Use -i=0 as a harmless way to do that.

RUN

shfmt *<file>*
Print the formatted script

shfmt -w *<file>*
Write the result back to the file

shfmt -d *<path>*
Show a diff, exit non-zero if different

shfmt -l *<path>*
List files whose formatting differs

shfmt -l -w .
Format everything under here

shfmt -
Read from stdin

shfmt -l=0 *<path>*
List files separated by NUL

shfmt --version
Show version

STYLE (PRINTER)

shfmt -i *<n>*
Indent with n spaces (0 = tabs)

STYLE (PRINTER) (cont.)

shfmt -ci
Indent case branches

shfmt -bn
Binary ops like && and | may start a line

shfmt -sr
Space after redirect operators

shfmt -bl
Opening brace, then and do on their own line

shfmt -kp
Keep column alignment padding

shfmt -mn
Minify the script

shfmt -i 2 -ci -bn
Roughly Google's shell style

DIALECT AND PARSING

shfmt -ln *<dialect>*
Set dialect: bash, posix, mksh, bats, zsh

shfmt -p
Shorthand for -ln=posix

shfmt -s
Simplify code where safe

shfmt --filename *<name>*
Name for stdin input

shfmt --detect *<mode>*
How to find files: default, exec or all

shfmt --apply-ignore
Always honor EditorConfig ignore rules

shfmt -f *<path>*
Print shell files found, no formatting

shfmt --to-json
Print the syntax tree as JSON

CONFIG (.EDITORCONFIG)

.editorconfig

```
[*.sh]
indent_style = space
indent_size = 2
case_indent = true
binary_next_line = true
space_redirects = true
language_dialect = bash
```

indent_style / indent_size
Same as -i

case_indent, binary_next_line
Same as -ci and -bn

[[shell]] section header
Match scripts by shebang, no extension

ignore = true
Skip a path when walking directories

RECIPES

CI check

```
# fails the job when anything
differs
shfmt -d -i 2 -ci .
```

Format only tracked scripts

```
git ls-files -z '*.sh' | xargs -0
shfmt -w
```

Syntax check instead of bash -n

```
shfmt -ln posix script.sh >/dev/
null
# prints line:col and error if
invalid
```

pre-commit hook

```
# .pre-commit-config.yaml
- repo: https://github.com/scop/
pre-commit-shfmt
  rev: v3.14.1-1
  hooks:
    - id: shfmt
```