socat Bidirectional byte relay

START HERE

`socat -` `TCP:<host>:<port>`
Talk to a TCP port

`socat TCP-LISTEN:<port>` `-`
Accept one connection

`socat TCP-LISTEN:<port>,` `fork,reuseaddr -`
Serve many clients

`socat TCP-` `LISTEN:<lport>,fork` `TCP:<host>:<port>`
Forward a port

`socat UNIX-` `LISTEN:<path>,fork -`
Listen on a Unix socket

`socat - UNIX-` `CONNECT:<path>`
Connect to a Unix socket

`socat -u TCP-` `LISTEN:<port>` `CREATE:<file>`
Receive a file

`socat -d -d <addr1>` `<addr2>`
See what it does

Address 1 TYPE:args,options → **both ways** → **socat** relay loop → **both ways** → **Address 2** TYPE:args,options

CONCEPTS

socat <addr1> <addr2> opens two endpoints and copies bytes both ways between them. Everything else is choosing the two addresses.

An address is TYPE:arg:arg,option,option=value. Options follow the commas; the type name is case-insensitive.

The first address that fails or hits EOF ends the relay. Add fork on a listener to keep serving, and shut-down or -t if the peer needs EOF.

Quote addresses that contain commas, spaces or shell characters. Use socat -V to see which address types your build supports.

BASICS

`socat <addr1> <addr2>`
Relay between two addresses

`socat - <addr>`
Connect stdin/stdout to an address

`socat -u <addr1> <addr2>`
One way only: first read, second write

`socat -d -d <addr1>` `<addr2>`
Log more: -d notices, -d -d info

`socat -v <addr1> <addr2>`
Dump transferred text to stderr

`socat -x <addr1> <addr2>`
Dump transferred data as hex to stderr

`socat -T <secs> <addr1>` `<addr2>`
Quit after this much inactivity

`socat -V`
Print version and built-in features

TCP AND UDP

`socat - TCP:<host>:<port>`
Connect to a TCP port

`socat TCP-LISTEN:<port> -`
Listen for one TCP connection

`socat TCP-LISTEN:<port>,` `fork,reuseaddr -`
Serve each client in a child process

TCP AND UDP (cont.)

`socat TCP-` `LISTEN:<port>,bind=<ip> -`
Listen on one local address only

`socat TCP-` `LISTEN:<port>,range=<cidr>` `-`
Accept only peers in a network

`socat - TCP4:<host>:<port>`
Force IPv4 (TCP6 forces IPv6)

`socat` `TCP:<host>:<port>,connect-` `timeout=<s> -`
Give up connecting after a while

`socat - UDP:<host>:<port>`
Send and receive UDP datagrams

`socat UDP-` `LISTEN:<port>,fork -`
Receive UDP datagrams, one peer per child

UNIX SOCKETS AND FILES

`socat UNIX-` `LISTEN:<path>,fork -`
Listen on a Unix socket

`socat - UNIX-` `CONNECT:<path>`
Connect to a Unix socket

`socat UNIX-` `LISTEN:<path>,mode=<mode>` `-`
Set permissions of the socket file

`socat UNIX-` `LISTEN:<path>,unlink-early` `-`
Remove a stale socket file first

`socat - GOPEN:<file>`
Open a file or socket, whichever it is

`socat - OPEN:<file>`
Read an existing file

`socat -u - CREATE:<file>`
Write stdin to a new file

`socat -u -` `OPEN:<file>,creat,append`
Append stdin to a file

FORWARD AND PROXY

`socat TCP-LISTEN:<lport>,` `fork,reuseaddr` `TCP:<host>:<port>`
Forward a local port to a remote one

FORWARD AND PROXY (cont.)

`socat TCP-LISTEN:<lport>,` `fork,bind=<ip>` `TCP:<host>:<port>`
Forward, listening on one address only

`socat UNIX-` `LISTEN:<path>,fork` `TCP:<host>:<port>`
Expose a TCP service as a Unix socket

`socat TCP-` `LISTEN:<port>,fork UNIX-` `CONNECT:<path>`
Expose a Unix socket over TCP

`socat TCP-LISTEN:<lport>,` `fork` `PROXY:<proxy>:<host>:<port>`
Connect through an HTTP proxy

`socat TCP-LISTEN:<lport>,` `fork` `SOCKS4A:<socks>:<host>:<port>`
Connect through a SOCKS4A proxy

`socat -v TCP-` `LISTEN:<lport>,fork` `TCP:<host>:<port>`
Forward and print the traffic

TLS

`socat -` `OPENSSL:<host>:<port>`
Connect over TLS (verifies the server)

`socat -` `OPENSSL:<host>:<port>,` `verify=0`
Connect over TLS, skip verification

`socat -` `OPENSSL:<host>:<p>,cafile=` `<c>`
Verify against a given CA file

`socat OPENSSL-LISTEN:<p>,` `cert=<f>,verify=0 -`
TLS server, no client cert needed

Without verify=0 the server demands a client certificate. <f> must hold key and cert, or add key=<key>.

`socat OPENSSL-LISTEN:<p>,` `cert=<f>,cafile=<c> -`
TLS server that requires client certs

`socat TCP-` `LISTEN:<lport>,fork` `OPENSSL:<host>:<port>`
Add TLS in front of a plain client

TLS (cont.)

`socat OPENSSL-LISTEN:<p>,` `cert=<f>,verify=0` `TCP:<host>:<port>`
Terminate TLS for a plain server

PROGRAMS AND TERMINALS

`socat TCP-` `LISTEN:<port>,fork` `EXEC:<prog>`
Run a program per connection

`socat TCP-` `LISTEN:<port>,fork` `SYSTEM:'<shell cmd>'`
Run a shell command per connection

`socat -` `EXEC:<prog>,pty,stderr`
Run a program on a pty with stderr merged

`socat -,raw,echo=0` `EXEC:'bash -` `i',pty,stderr,setsid`
Full interactive shell over a pty

`socat -,raw,echo=0 <addr>`
Raw local terminal, no echo

`socat` `PTY,link=<path>,raw,echo=0` `<addr>`
Create a pty device linked at a path

RECIPES

Send a file between hosts

```
# receiver
socat -u TCP-LISTEN:5000
CREATE:in.tar
# sender
socat -u OPEN:in.tar
TCP:<host>:5000
```

Watch traffic through a forward

```
socat -v TCP-LISTEN:8080,fork \
  TCP:example.com:80
# other shell
curl localhost:8080/
```

Spy on a Unix socket

```
socat -v UNIX-LISTEN:s.sock,\
  mode=600,fork \
  UNIX-CONNECT:/run/docker.sock
# then, in another shell
curl --unix-socket s.sock \
  http://localhost/version
```

Quick TLS test server

```
openssl req -x509 -newkey \
  rsa:2048 -nodes -subj \
  /CN=localhost \
  -keyout k.pem -out c.pem
cat k.pem c.pem > both.pem
socat OPENSSL-LISTEN:4433,\
  cert=both.pem,verify=0,fork -
# other shell
socat - OPENSSL:localhost:4433,
\
  verify=0
```