SOPS Encrypted secrets files

CONCEPTS

sops encrypts the values and leaves keys readable, so encrypted YAML/JSON files still diff and review well in git.

Plaintext file YAML, JSON, ENV, INI
↓ encrypt / edit
Data key AES256-GCM per file
↓ wrapped by
Master keys age, PGP, KMS, Vault

Each file has one random data key; master keys (age, PGP, cloud KMS) only wrap it, so you can add or remove people without re-encrypting values.

Commit .sops.yaml next to the secrets: it picks keys by file path so nobody has to remember flags.

EDIT & READ

`sops edit <file>`
Edit a file in your editor, re-encrypting on save

`sops decrypt <file>`
Print the decrypted file to stdout

`sops decrypt -i <file>`
Decrypt a file in place

`sops decrypt --extract '["<key>"][<n>]' <file>`
Print a single value

`sops decrypt --output <out> <file>`
Write plaintext to another file

`sops decrypt --output-type json <file>`
Convert format while decrypting

ENCRYPT

`sops encrypt -i <file>`
Encrypt in place using .sops.yaml rules

`sops encrypt <file> > <out>`
Encrypt to a new file

`sops encrypt --age <recipient> <file>`
Encrypt to age recipients

ENCRYPT (cont.)

`sops encrypt --pgp <fingerprint> <file>`
Encrypt to PGP keys

`sops encrypt --kms <arn> <file>`
Encrypt with AWS KMS keys

`sops encrypt --encrypted-regex '^(data|stringData)$' <file>`
Encrypt only keys matching a regex

`sops encrypt --unencrypted-regex '<regex>' <file>`
Leave matching keys in plain text

`sops encrypt --input-type <type> --output-type <type> <file>`
Force formats (json, yaml, dotenv, ini, binary)

CHANGE VALUES

`sops set <file> '["a"]["b"]' '"<value>"'`
Set a value; value is JSON

`sops set --value-stdin <file> '["a"]["b"]'`
Read the value from stdin

`sops unset <file> '["a"]["b"]'`
Delete a key

RUN WITH SECRETS

`sops exec-env <file> '<cmd>'`
Run a command with values as env vars

`sops exec-file <file> '<cmd> {}'`
Run a command with a temp file path in {}

`sops decrypt --output-type dotenv <file>`
Print as KEY=value lines

KEYS & CONFIG

`sops updatekeys <file>`
Sync a file's keys with .sops.yaml

`sops updatekeys -y <file>`
Same, without the confirmation prompt

KEYS & CONFIG (cont.)

`sops rotate -i <file>`
New data key, re-encrypt all values

`sops rotate -i --add-age <recipient> <file>`
Add an age recipient while rotating

`sops rotate -i --rm-age <recipient> <file>`
Remove an age recipient

`sops --config <path> <command>`
Use a specific config file

ENVIRONMENT

`SOPS_AGE_KEY_FILE=<path>`
Age identity file for decryption

`SOPS_AGE_KEY=<key>`
Age secret key given directly

`SOPS_AGE_RECIPIENTS=<list>`
Age recipients to encrypt to

`SOPS_EDITOR=<editor>`
Editor for sops edit

On macOS the default age key path is ~/Library/Application Support/sops/age/keys.txt; Linux uses ~/.config/sops/age/keys.txt.

.SOPS.YAML

Creation rules (first match wins)

```
creation_rules:
  - path_regex: \.prod\.yaml$
    age: age1prod...,age1admin...
  - path_regex: secrets/.*
    age: age1dev...
    encrypted_regex: '^(data|
stringData)$'
  - age: age1admin...
```

A rule without path_regex matches everything, so put it last. Run sops updatekeys after changing recipients on existing files.

Other rule keys: kms, gcp_kms, azure_keyvault, hc_vault_uris, pgp, unencrypted_regex, encrypted_suffix.