# SQLAlchemy Python SQL toolkit

**START HERE**

**`create_engine("<url>")`**
Connect to a database

**`class User(Base)`**
Map a table to a class

**`Base.metadata.create_all(engine)`**
Create the tables

**`with Session(engine) as s:`**
Open a unit of work

**`s.add(obj)`**
Queue an INSERT

**`s.scalars(select(User))`**
Query objects

**`s.commit()`**
Flush and save

**`relationship()`**
Link two classes

**Engine** URL + pool → `connect` → **Connection** Core, raw SQL → `wraps` → **Session** ORM unit of work → `tracks` → **Mapped objects** identity map

## CONCEPTS

Core is SQL as Python expressions (Engine, Connection, Table). The ORM adds mapped classes and the Session on top.

Nothing is saved until commit(). Leaving the with-block without commit rolls back.

## ENGINE

**`create_engine("sqlite:///app.db")`**
SQLite file engine

**`create_engine("postgresql+psycopg://<user>:<pw>@<host>/<db>")`**
PostgreSQL engine
*Format is dialect+driver://user:password@host:port/database.*

**`create_engine("sqlite://", echo=True)`**
In-memory DB, log all SQL

**`from sqlalchemy import text`**
Wrap a raw SQL string

**`with engine.connect() as conn:`**
Core connection block
*Autobegin: call conn.commit() to save; nothing is committed on exit.*

**`conn.execute(text("SELECT 1"))`**
Run raw SQL

## ENGINE (cont.)

**`conn.execute(text("... :id"), {"id": 5})`**
Bind parameters by name
*Never format values into the string; use bound parameters.*

**`with engine.begin() as conn:`**
Connection that commits on exit

## DECLARE MODELS

**`class Base(DeclarativeBase): pass`**
Declarative base class

**`__tablename__ = "user"`**
Table name for a model

**`id: Mapped[int] = mapped_column(primary_key=True)`**
Primary key column

**`name: Mapped[str] = mapped_column(String(50))`**
Typed string column

**`email: Mapped[Optional[str]]`**
Nullable column
*Mapped[str] means NOT NULL; Optional makes it nullable.*

**`mapped_column(unique=True, index=True)`**
Unique constraint / index

## DECLARE MODELS (cont.)

**`mapped_column(ForeignKey("user.id"))`**
Foreign key column

**`Base.metadata.create_all(engine)`**
Create missing tables
*Does not alter existing tables; use Alembic for that.*

## SESSION

**`with Session(engine) as session:`**
Open a session

**`session.add(<obj>)`**
Add one object

**`session.commit()`**
Write changes and end transaction

**`session.rollback()`**
Discard pending changes

**`session.get(User, <pk>)`**
Fetch by primary key

**`sessionmaker(engine)`**
Session factory for an app

## QUERY

**`session.scalars(select(User)).all()`**
All rows as objects

**`select(User).where(User.name == "ann")`**
Filter rows

## QUERY (cont.)

**`session.scalars(stmt).first()`**
First object or None

**`session.execute(select(User.id, User.name))`**
Rows of column tuples

**`select(User).order_by(User.name.desc())`**
Sort rows

**`.where(or_(<a>, <b>))`**
OR conditions

**`select(Order.user_id, func.sum(Order.total)).group_by(Order.user_id)`**
Aggregate per group

## INSERT, UPDATE, DELETE

**`user.name = "bob"`**
Update via attribute, then commit

**`update(User).where(<cond>).values(name="x")`**
Bulk UPDATE

## RELATIONSHIPS

**`posts: Mapped[list["Post"]] = relationship(back_populates="author")`**
One-to-many side

**`author: Mapped["User"] = relationship(back_populates="posts")`**
Many-to-one side

## RELATIONSHIPS (cont.)

**`relationship(cascade="all, delete-orphan")`**
Delete children with parent

**`select(User).options(selectinload(User.posts))`**
Eager-load collection
*Avoids the N+1 query pattern.*

**`select(Post).options(joinedload(Post.author))`**
Eager-load by JOIN

## JOINS

**`select(User, Post).join(Post)`**
Inner join on the foreign key

**`select(User).join(User.posts)`**
Join along a relationship

## ALEMBIC MIGRATIONS

**`alembic init <dir>`**
Create migration environment

**`target_metadata = Base.metadata`**
Set in env.py for autogenerate

**`alembic revision --autogenerate -m "<msg>"`**
Diff models against DB
*Review the generated file: renames show up as drop + add.*

**`alembic upgrade head`**
Apply all migrations

## ALEMBIC MIGRATIONS (cont.)

**`alembic downgrade -1`**
Undo the last migration

## RECIPES

### Minimal ORM app

```
class Base(DeclarativeBase):
pass
class User(Base):
    __tablename__ = "user"
    id: Mapped[int] =
mapped_column(primary_key=True)
    name: Mapped[str]
engine = create_engine(
"sqlite:///app.db")
Base.metadata.create_all(
engine)
```

### Insert and read back

```
with Session(engine) as s:
    s.add(User(name="ann"))
    s.commit()
    for u in
s.scalars(select(User)):
        print(u.id, u.name)
```

### Users with post counts

```
stmt = (select(User.name,
func.count(Post.id))
    .join(User.posts,
isouter=True)
    .group_by(User.id))
rows =
session.execute(stmt).all()
```

### Session per request

```
SessionLocal =
sessionmaker(engine)
def get_db():
    with SessionLocal() as s:
        yield s
```