SQLAlchemy Python SQL toolkit

CONCEPTS

Core is SQL as Python expressions (Engine, Connection, Table). The ORM adds mapped classes and the Session on top.

ENGINE

`create_engine("sqlite:///app.db")`
SQLite file engine

`create_engine("postgresql+psycopg://<user>:<pw>@<host>/<db>")`
PostgreSQL engine

`with engine.connect() as conn:`
Core connection block

`conn.execute(text("... :id"), {"id": 5})`
Bind parameters by name

DECLARE MODELS

`class Base(DeclarativeBase): pass`
Declarative base class

`__tablename__ = "user"`
Table name for a model

`id: Mapped[int] = mapped_column(primary_key=True)`
Primary key column

`name: Mapped[str] = mapped_column(String(50))`
Typed string column

`mapped_column(ForeignKey("user.id"))`
Foreign key column

`Base.metadata.create_all(engine)`
Create missing tables

SESSION

`with Session(engine) as session:`
Open a session

`session.add(<obj>)`
Add one object

`session.commit()`
Write changes and end transaction

`session.get(User, <pk>)`
Fetch by primary key

QUERY

`session.scalars(select(User)).all()`
All rows as objects

`select(User).where(User.name == "ann")`
Filter rows

`session.scalars(stmt).first()`
First object or None

`select(User).order_by(User.name.desc())`
Sort rows

INSERT, UPDATE, DELETE

`user.name = "bob"`
Update via attribute, then commit

RELATIONSHIPS

`posts: Mapped[list["Post"]] = relationship(back_populates="author")`
One-to-many side

`author: Mapped["User"] = relationship(back_populates="posts")`
Many-to-one side

`select(User).options(selectinload(User.posts))`
Eager-load collection

JOINS

`select(User, Post).join(Post)`
Inner join on the foreign key

`select(User).join(User.posts)`
Join along a relationship

ALEMBIC MIGRATIONS

`alembic init <dir>`
Create migration environment

`target_metadata = Base.metadata`
Set in env.py for autogenerate

`alembic revision --autogenerate -m "<msg>"`
Diff models against DB

`alembic upgrade head`
Apply all migrations