SQLite CLI

Shell for SQLite

Input file, SQL arg, stdin → `-cmd` `-init` → **Shell** dot-commands + SQL → `.mode` `.headers` → **Formatter** box, csv, json... → `.once` `.output` → **Output** stdout, file or pipe

CONCEPTS

Dot-commands are shell commands, not SQL: they sit alone on one line, need no semicolon and cannot be used from a library. SQL statements need a closing ;.

Without a filename (or with :memory:) you get a temporary database that vanishes on exit. Use .save <file> to keep it.

OPEN AND RUN

`sqlite3` *`<file.db>`*
Open (or create) a database

`sqlite3` *`<file.db>`* **`"`***`<sql>`***`"`**
Run one statement and exit

`sqlite3` *`<file.db>`* **`<`** *`<script.sql>`*
Run a SQL script

`.read` *`<script.sql>`*
Run a script from inside the shell

`.open` *`<file.db>`*
Switch to another database file

`sqlite3 -readonly` *`<file.db>`*
Open without write access

OPEN AND RUN (cont.)

`.help`
List all dot-commands

`.quit`
Exit the shell

`.shell` *`<cmd>`*
Run a shell command

OUTPUT MODES

`.mode box`
Unicode box table

`.mode column`
Aligned plain columns

`.mode table`
ASCII table

`.mode markdown`
Markdown table

`.mode csv`
Comma separated values

`.mode json`
JSON array of objects

`.mode line`
One column per line

`.mode list`
Default pipe-separated

`.headers on`
Print column names

`.nullvalue` *`<text>`*
Show NULL as text

OUTPUT MODES (cont.)

`.show`
Show current settings

INSPECT SCHEMA

`.tables`
List tables and views

`.tables` *`<pattern>`*
Filter with a LIKE pattern

`.schema`
All CREATE statements

`.schema` *`<table>`*
CREATE statements for one table

`.schema --indent`
Pretty-printed schema

`.indexes` *`<table>`*
List indexes

`.databases`
Attached databases and files

`pragma table_info(`*`<table>`***`);`**
Columns and types

IMPORT AND EXPORT

`.import --csv` *`<file>`* *`<table>`*
Load CSV into a table

IMPORT AND EXPORT (cont.)

`.import --csv --skip 1` *`<file>`* *`<table>`*
Load into an existing table

`.once` *`<file>`*
Send next result to a file

`.output` *`<file>`*
Send all results to a file

`.output`
Back to stdout

BACKUP AND RECOVER

`.backup` *`<file>`*
Binary copy of main database

`.restore` *`<file>`*
Load a backup into this database

`.save` *`<file>`*
Write database to a file

`.dump`
Whole database as SQL text

`.dump` *`<table>`*
One table as SQL text

`sqlite3` *`<old.db>`* **`.dump |`** **`sqlite3`** *`<new.db>`*
Rebuild into a fresh file

`pragma integrity_check;`
Check for corruption

DEBUG AND TUNE

`.timer on`
Time each statement

`.eqp on`
Show query plan automatically

`explain query plan` *`<sql>`***`;`**
Plan for one statement

RECIPES

CSV into a new database

```
sqlite3 app.db
# inside the shell:
.import --csv people.csv
people
.schema people
select count(*) from people;
```

Export a query to CSV

```
sqlite3 -header -csv app.db
"select * from people" >
people.csv
# or inside the shell:
.headers on
.mode csv
.once people.csv
select * from people;
```

Safe live backup

```
sqlite3 app.db ".backup
'snap.db'"
sqlite3 snap.db "pragma
integrity_check;"
```