stern Multi-pod Kubernetes logs

CONCEPTS

stern tails many pods and containers at once, one colour per pod, and picks up new or restarted pods automatically. The query is a regular expression on the pod name, not a glob.

Pod query regex or kind/name
↓ `-n -l --node`
Pods namespaces, labels
↓ `-c -E --container-state`
Containers init, ephemeral
↓ `-i -e --since`
Log lines merged stream
↓ `-o --template`
Output colour, JSON, custom

Default is all pods you can see in the current namespace and context; --since defaults to 48h and --tail to all lines, so busy pods print a lot at start.

SELECTING PODS

`stern <query>`
Tail pods whose name matches regex

`stern .`
Tail every pod in the namespace

`stern <kind>/<name>`
Exact resource, e.g. deployment/nginx

`-n <ns> / --namespace <ns>`
Namespace, repeat or comma-separate

`-A / --all-namespaces`
Every namespace

`-l <selector> / --selector`
Filter by label selector

`--field-selector <expr>`
Filter by field, e.g. spec.nodeName=<node>

`--node <name>`
Pods on one node

`--exclude-pod <regex>`
Skip pods matching regex

`--condition <name[=value]>`
Pods by condition, e.g. ready=false

`-p / --prompt`
Pick app.kubernetes.io/instance interactively

CONTAINERS

`-c <regex> / --container`
Only containers matching regex

`-E <regex> / --exclude-container`
Skip containers, e.g. istio-proxy

`--container-state <state>`
running, waiting, terminated or all

`--init-containers=false`
Leave out init containers

`--ephemeral-containers=false`
Leave out ephemeral containers

TIME AND VOLUME

`--tail <n>`
Last n lines per container

`-s <dur> / --since <dur>`
Logs newer than e.g. 15m or 2h

`--no-follow`
Print and exit, do not stream

`-t / --timestamps`
Prefix timestamps

`--timestamps=short`
Shorter timestamp format

`--timezone <tz>`
Show timestamps in e.g. Asia/Tokyo

`--max-log-requests <n>`
Limit concurrent log streams

FILTERING LINES

`-i <regex> / --include`
Show only matching lines

`-e <regex> / --exclude`
Hide matching lines

`-H <regex> / --highlight`
Highlight matches, keep all lines

`--only-log-lines`
Drop the pod/container prefix noise

OUTPUT AND COLOUR

`-o raw`
Message text only, no prefix

`-o json`
One JSON object per line

`-o extjson / ppextjson`
Extended or pretty-printed JSON

OUTPUT AND COLOUR (cont.)

`--template '<go-template>'`
Custom line format

`-T <file> / --template-file`
Template read from a file

`--color auto|always|never`
Force or disable colour

`-d / --diff-container`
Separate colour per container

CLUSTER AND CONFIG

`--context <name>`
Use another kubeconfig context

`--kubeconfig <path>`
Use another kubeconfig file

`--config <path>`
Config file, default ~/.config/stern/config.yaml

`--stdin`
Read logs from stdin, colour only

`--completion bash|zsh|fish`
Print shell completion code

`-v / --version`
Print version

`kubectl krew install stern`
Install as kubectl plugin

Put defaults such as tail: 10 or timestamps: short into the config file as flag-name: value pairs.

RECIPES

Errors across a deployment, recent

```
stern deployment/api -n prod --since 15m -i 'error|panic' -e healthcheck
```

Pretty JSON logs through jq

```
stern api -n prod -o raw --tail 0 | jq -R 'fromjson? | select(.level=="error")'
```

Debug a rollout, new lines only

```
kubectl rollout restart deploy/api -n prod
stern api -n prod --tail 0 -t=short -E istio-proxy
```

Custom line with namespace and pod

```
stern . -A -l app=web --template '{{.Namespace}}/{{.PodName}} {{.Message}}{{"\n"}}'
```